Pulse Secure®

Pulse Connect Secure/Pulse Policy Secure

REST API Solutions Guide

Published Date **August 2020**
Document Revision **8.5.1**

Pulse Secure, LLC

2700 Zanker Road, Suite 200
San Jose, CA 95134

https://www.pulsesecure.net

Pulse Secure assumes no responsibility for any inaccuracies in this document. Pulse Secure reserves the right to change, modify, transfer, or otherwise revise this publication without notice.

Products made or sold by Pulse Secure or components thereof might be covered by one or more of the following patents that are owned by or licensed to Pulse Secure: U.S. Patent Nos. 5,473,599, 5,905,725, 5,909,440, 6,192,051, 6,333,650, 6,359,479, 6,406,312, 6,429,706, 6,459,579, 6,493,347, 6,538,518, 6,538,899, 6,552,918, 6,567,902, 6,578,186, and 6,590,785.

REST API Solutions Guide

Copyright © 2020, Pulse Secure, LLC. All rights reserved.

Printed in USA.

Revision History

Document Version	Revision Summary
8.5.1	Updated the following sections with curl command: - Exporting TOTP Users from One Device to Another Device - Importing TOTP Users from One Device to Another Device - Getting Active Sessions - Getting Particular Active Session Details - Deleting a Particular Active Session - Deleting All Active Sessions
8.5	Added the following section for 9.1R8 release: PCS-specific - Resetting TOTP User - Unlocking TOTP User PPS-specific - Getting Authentication API Key - Pulse Policy Secure Alert Based Admission Control APIs
8.4	Added the following section for 9.1R7 release: - Retrieving Serial Number and Machine ID
8.3	Added the following section for 9.1R6 release: - Enabling/Disabling ICE License - Getting the Current Status of ICE License
8.2.1	Added the following section for 9.1R5 release: - Fetching Active Number of HTML5 Sessions
8.2	Updated the following section for 9.1R5 release: - Getting License Report from License Server
8.1	Updated Profiler REST APIs URL
8.0	Added/Updated the following sections for 9.1R4 release: - Getting Active Sessions - Getting System Information - Fetching the User Login Statistics - Health Check Status - VIP Failover - Applying License - Deleting License - Getting License Clients - Getting License Report from License Server - Profiler REST APIs
7.1	Removed the unused header “Postman-Token” from the Guide.
7.0	Updated the “PCS/PPS Configuration Using REST APIs” section with: - Export without ESAP and Pulse Client packages API. - Backup/restore binary configuration - Added sample curl commands
6.0	Updated the “PCS/PPS Configuration Using REST APIs” section with IF MAP related REST APIs.
5.1	Updated the “PCS/PPS Configuration Using REST APIs” section with AD and LDAP related REST APIs.
5.0	Updated with “PCS/PPS Configuration Using REST APIs” section.

© 2020 by Pulse Secure, LLC. All rights reserved

Contents

REVISION HISTORY 3

OVERVIEW 7

AUTHENTICATION FOR REST APIS 8
Basic Authentication using the HTTP Authorization Header 8
Realm-based Authentication (Recommended) 11
SAMPLE GET/POST/PUT/DELETE REQUEST AND RESPONSES IN PCS 13
GET API Call: Fetch the Specific User under Local Authentication Server 13
POST API Call: Create User for Existing Local Authentication Server 14
PUT API Call: Update Full name field of Specific user 15
DELETE API Call: DELETE Specific User 17
Representing Configuration Resources Using Links 19
SAMPLE GET/POST/PUT/DELETE REQUEST AND RESPONSES IN PPS 20
GET API Call: Fetch the Details under Endpoint Policy 20
POST API Call: Create an SRX Enforcer in Infranet Enforcer Connection 21
PUT API Call: Update Existing Configuration Where In Initial Location Group is Configured as Guest 23
DELETE API Call: Delete an SNMP Device 24

PCS/PPS CONFIGURATIONS USING REST APIS 26

GETTING ACTIVE SESSIONS 27
GETTING PARTICULAR ACTIVE SESSION DETAILS 28
DELETING A PARTICULAR ACTIVE SESSION 29
DELETING ALL ACTIVE SESSIONS 29
QUERYING SET OF LEASED LICENSES IN THE LICENSE SERVER SYSTEM 30
PULLING STATE FROM A LICENSE SERVER ON A LICENSE CLIENT 32
CONFIGURING CERTIFICATES BASED ON CSR WORKFLOW 33
CREATING A CSR FOR A DEVICE CERTIFICATE 35
DELETING DEVICE CERTIFICATE BY ITS SUBJECT NAME 36
GETTING SYSTEM INFORMATION 36
RETRIEVING SERIAL NUMBER AND MACHINE ID 37
REALM-BASED ADMINISTRATOR USER USING ADMINISTRATOR LOCAL AUTHENTICATION SERVER 38
REALM-BASED ADMINISTRATOR USER USING AD AUTHENTICATION SERVER 39
REALM-BASED ADMINISTRATOR USER USING LDAP AUTHENTICATION SERVER 39
REALM-BASED ADMINISTRATOR USER USING RADIUS AUTHENTICATION SERVER 40
REALM-BASED ADMINISTRATOR USER FROM A PARTICULAR SOURCE IP 40
REALM-BASED ADMINISTRATOR AUTHORIZATION ROLE MAPPING TO .ADMINISTRATOR ROLE 41
SPECIFYING SESSION VALIDITY FOR REST ADMIN SESSION 42
GETTING ACTIVE DIRECTORY SEARCH GROUPS 43
ADDING SEARCH GROUP TO ACTIVE DIRECTORY 44
UPDATING ACTIVE DIRECTORY GROUP 45
DELETING ACTIVE DIRECTORY GROUPS 46
GETTING ALL LDAP GROUP LIST 47
ADDING GROUPS TO LDAP 47
UPDATING LDAP SOURCE GROUP 48
DELETING LDAP SOURCE GROUP 49
CREATING A CLUSTER 50

© 2020 by Pulse Secure, LLC. All rights reserved

Adding a Member to Cluster....51
Getting Cluster Status....51
Deleting Cluster Member....53
Getting Health Check Status....54
Joining a Cluster....55
VIP Failover....56
Configuring IF MAP Server....56
Configuring IF MAP Client....57
Configuring No IF MAP Server....58
Getting Config Without Pulse Packages (ESAP and Pulse Client Packages)....59
Backing Up Binary Configuration....60
Restoring Binary Configuration (import=normal)....60
Restoring Binary Configuration (import=full)....62

PCS-SPECIFIC CONFIGURATIONS USING REST APIS....64

Creating a VLAN....65
Deleting a VLAN....66
Creating a User Role....66
Fetching the User Login Statistics....68
Updating the User Role Settings....69
Deleting a User Role....71
Creating a User Realm....71
Deleting a User Realm....75
Creating a Resource Profile....75
Deleting a Resource Profile....77
Creating a Resource Policy....78
Fetching a Resource Policy....79
Deleting a Resource Policy....80
Creating an AD Authentication Server....80
Deleting an AD Authentication Server....82
Creating an LDAP Authentication Server....82
Creating a Radius Server....85
Modifying Radius Server Details....87
Creating Sign-In-Policy....88
Deleting Sign-in-Policy....89
Disabling Sign-in-URL....89
Creating a Web Bookmark for a Role....90
Reordering....91
Fetching the Resource with Multiple Identifiers....92
Updating Resource Identified Using Multiple Identifiers....93
Fetching Active Number of HTML5 Sessions....94
Updating Password in Clear Text....94
Applying Authcode and Downloading Licenses from PCLS on VA-SPE|PSA-V....95
Applying License....96
Deleting License....97
Getting License Clients....98
Getting License Report from License Server....100
Enabling/Disabling ICE License....104
Getting the Current Status of ICE License....105
Exporting TOTP Users from One Device to Another Device....105
Importing TOTP Users from One Device to Another Device....106
Resetting TOTP User....106
Unlocking TOTP User....107

© 2020 by Pulse Secure, LLC. All rights reserved

Sample Error Responses 108
400 BAD REQUEST 108
403 Forbidden 111
404 NOT FOUND 111
422 UNPROCESSABLE ENTITY 113
Limitations 114

PPS-SPECIFIC CONFIGURATIONS USING REST APIS 115

Creating the HC Policy 116
Deleting the HC Policy 117
Creating the Infranet Enforcer 118
Deleting the Infranet Enforcer 118
Creating a Resource Policy 119
Deleting a Resource Policy 119
Creating a RADIUS Client 120
Deleting a RADIUS Client 120
Creating a RADIUS Attribute Policy 121
Deleting a RADIUS Attribute Policy 121
Creating SNMP Device 122
Deleting SNMP Device 123
Creating SNMP Policy 123
Deleting SNMP Policy 124
Creating Device Group - TACACS+ 124
Deleting Device Group- TACACS+ 124
Creating TACACS+ Client 125
Deleting TACACS+ Client 125
Creating Shell Policies 126
Deleting Shell Policies 126
Creating Admission Control Client 127
Deleting Admission Control Client 127
Creating Admission Control Policy 127
Deleting Admission Control Policy 128
Getting Authentication API Key 128
Pulse Policy Secure Alert Based Admission Control APIs 129
Checking Status of PPS Server 129
Getting Session Details for Endpoint Based on IP Address 129
Getting Session Details for Endpoint Based on MAC Address 129
Sending Alert Event to PPS 129
Profiler REST APIs 130
Approving Devices 130
Updating Device Attributes 130

© 2020 by Pulse Secure, LLC. All rights reserved

Overview

The REST API provides a standardized method for Next-Gen firewalls, NAC devices, and third-party systems to interact with PCS/PPS. Representational state transfer (REST) or RESTful Web services are one way of providing interoperability between computer systems on the Internet. REST-compliant Web services allow requesting systems to access and manipulate textual representations of Web resources using a uniform and predefined set of stateless operations. In a RESTful Web service, requests made to a resource's URI will elicit a response that may be in XML, HTML, JSON or some other defined format. PCS/PPS supports JSON format only.

REST methods determine the HTTP method for manipulating the resources defined in the service operation. The kind of operations available include those predefined by the HTTP verbs GET, POST, PUT, DELETE and so on. The response may confirm that some alteration has been made to the stored resource, and it may provide hypertext links to other related resources or collections of resources. By making use of a stateless protocol and standard operations, REST systems aim for fast performance, reliability, and the ability to grow, by re-using components that can be managed and updated without affecting the system as a whole, even while it is running.

Note: REST API Support for PCS/PPS involves only Configuration APIs. Also, PCS/PPS supports only the GET, POST, PUT and DELETE APIs.

The valid and supported values are described in the Table 1.

Table 1: Valid and Supported Values

HTTP Verb	Definition
DELETE	Delete an existing resource.
GET	Retrieve a representation of a resource.
POST	Create a new resource
PUT	Create a new resource to a new URL or modify an existing resource to an existing URL.

The error codes supported are described in the Table 2.

Table 2: Error Codes Supported

HTTP Verb	Definition
200 OK	Requesting for resource information successful using GET Resource update successful using PUT
201 Created	Resource creation successful using POST
204 No Content	Deletion of resource successful with no body. Even PUT, POST may return 204 if no errors or warnings seen
400 – Bad Request	Any Request (GET/PUT/POST/DELETE, and so on) is invalid. Example: Incorrect JSON format

© 2020 by Pulse Secure, LLC. All rights reserved

HTTP Verb	Definition
401 – Unauthorized	Any REST Call with invalid credentials
403 – Forbidden	REST Call with valid credentials but no permission
404 – Not found	Requested resource in URI does not exist
422 – Unprocessable Entity	Any validation/referential integrity errors that would result in failure of PUT/POST/DELETE request
500 Server Error	When PCS/PPS rest server is not responding

Authentication for REST APIs

Basic authentication using the HTTP authorization header is used to authenticate username/password on the Administrators auth. server. It is expected that the user is already configured in the Administrators auth. server. On a successful login, a random token (api_key) is generated **once** and sent back as a JSON response. Further access to APIs can use this api_key value as username and password as empty in their Authorization header for access.

Note: A new random api_key is generated on a successful login. The user can continue to use this key till the administrator:

- Enables/disables the user account
- Enables/disables the Allow REST API feature for that user

Basic Authentication using the HTTP Authorization Header

Configurations for REST APIs

The configuration of PCS/PPS can be accessed using REST APIs. The PCS/PPS configuration is represented in a json form when accessed using REST APIs. The structure of the JSON representation is very similar to the structure of PCS/PPS XML configuration.

A new admin UI option for users under "Administrators" authserver has been added. REST API authentication would be successful only for those users who have this option enabled.

REST API access can be enabled from Pulse Connect Secure Admin console as shown below or from Pulse Connect Secure serial console.

© 2020 by Pulse Secure, LLC. All rights reserved

To enable this check box in Pulse Connect Secure Admin Console:

1. Go to Authentication > Auth. Servers >Administrators > Update Administrator admin1.
2. Select the Allow access to REST APIs check box. See figure below.
3. Click Save Changes.



Enabling REST API Access for an Administrator from the Serial Console

REST API access for an administrator user can be enabled during initial configuration and while creating a new administrator user.

During initial provisioning, there are no administrator accounts configured and the system prompts to create a new administrator user. For the option "Do you want to enable REST API access for this administrator (y/n):", enter y.

Note: Any characters other than "y" or "n" are invalid responses.



© 2020 by Pulse Secure, LLC. All rights reserved

When creating a new administrator user from the console using the option "2. Create admin username and password", for the option "Do you want to enable REST API access for this administrator (y/n):", enter y.



The entire communication is over TLS. An example is explained below:

REQUEST

```
GET /api/v1/auth HTTP/1.1

Host: 10.209.112.106

Authorization: Basic YWRtaW5kYjpkYW5hMTIz

Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK

Content-Type: application/json

Expires: -1

Keep-Alive: timeout=15

{ "api_key": "p5mMlc7RQu81R2NvssLCCZhP05kf0N2ONFeYeLXX6aU=" }
```

© 2020 by Pulse Secure, LLC. All rights reserved

Equivalent Curl Command

Note: While using curl command, ensure appropriate server CA certs is installed in the cert store recognized by curl. The sample curl commands provided in this document assumes you have appropriate server CA certs installed.

```
COMMAND

curl -i -u admindb:dana123 -G https://<hostname>/api/v1/auth

RESPONSE

HTTP/1.1 200 OK

Content-Type: application/json

{"api_key":"p9/h85ytEmkDzvkGSmQ4z77p6Ya7aLIC42vh0F9CGaQ="}


api_key received in response to authentication request should be used as
Username with EMPTY password in all future requests. Refer to the
examples in Sample GET/POST/PUT/DELETE Request and Responses in PCS.
```

Realm-based Authentication (Recommended)

Pulse Secure recommends realm-based authentication instead of basic authentication using the HTTPS authorization header.

```
REQUEST

POST /api/v1/realm_auth HTTP/1.1

Host: 10.209.116.214

Content-Type: application/json

Authorization: Basic YWRtaW46ZGFuYTEyMw==

{

  "realm": "adminrealm"

}

RESPONSE

HTTP/1.1 200 OK

content-type →application/json

{

    "api_key": "NjQzOGU0N2I5MDUyMWZhZWM0NmZiMTMxY2U3M2YyM2Q="

}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Authorization header for all future requests should perform Basic Auth using above api_key value as username and password as empty.

```
REQUEST

GET /api/v1/configuration HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
cDVtTWxjN1JRdTgxUjJOdnNzTENDWmhQMDVrZjBOMk9ORmVZZUxYWDZhVT06

RESPONSE

HTTP/1.1 200 OK

Content-Length →283

Content-Type →application/json

{

"administrators":

{ "href": "/api/v1/configuration/administrators" }

,

"authentication":

{ "href": "/api/v1/configuration/authentication" }

,

"system":

{ "href": "/api/v1/configuration/system" }

,

"users":

{ "href": "/api/v1/configuration/users" }

}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Sample GET/POST/PUT/DELETE Request and Responses in PCS

Below is a sample of GET/POST/PUT/DELETE request and responses:

GET API Call: Fetch the Specific User under Local Authentication Server

```
REQUEST

GET /api/v1/configuration/authentication/auth-servers/auth-server/Sys-
Local/local/users/user/user0001 HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
cDkvaDg1eXRFbWtEenZrR1NtUTR6NzdwNllhN2FMSUM0MnZoMEY5Q0dhUT06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length: 309

Content-Type: application/json

{

    "change-password-at-signin": "false",

    "console-access": "false",

    "enabled": "true",

    "fullname": "user0001",

    "one-time-use": "false",

    "password-encrypted":
"3u+UR6n8AgABAAAATjgR31G4neKag2hxI+wjaNsRRZGD6wMQVkLEQv+DPQZdUrQi5IWPuihJ
f8tnrsBV0XCQly6WgZ79Jv1fyzmssg==",

    "username": "user0001"

}
```

Equivalent Curl Command

```
COMMAND

curl -i -u p9/h85ytEmkDzvkGSmQ4z77p6Ya7aLIC42vh0F9CGaQ=: -X GET
https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user/user0001

RESPONSE

HTTP/1.1 200 OK

Content-Type: application/json

Content-Length: 303

{

  "change-password-at-signin": "false",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
  "console-access": "false",
  "enabled": "true",
  "fullname": "user0001",
  "one-time-use": "false",
  "password-encrypted":
"3u+UR6n8AgABAAAAOrKwtwwYUZlizIhEaq54tt550UA39gKEP8AQ7sjr/WTdtPLf36
mpsI5zGWpORVRjEIFAzVOvmxwgXVLBEJnIRQ==",
  "username": "user0001"
}
```

POST API Call: Create User for Existing Local Authentication Server

REQUEST

```
POST /api/v1/configuration/authentication/auth-servers/auth-server/Sys-
Local/local/users/user HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
cDkvaDg1eXRFbWtEenZrR1NtUTR6NzdwNllhN2FMSUM0MnZoMEY5Q0dhUT06

Content-Type: application/json

{
  "change-password-at-signin": "false",
  "console-access": "false",
  "enabled": "true",
  "fullname": "user0001",
  "one-time-use": "false",
  "password-encrypted":
"3u+UR6n8AgABAAAATjgR31G4neKag2hxI+wjaNsRRZGD6wMQVkLEQv+DPQZdUrQi5IWPuihJ
f8tnrsBV0XCQly6WgZ79Jv1fyzmssg==",
  "username": "user0001"
}
```

RESPONSE

```
HTTP/1.1 200 OK

Content-Length: 122

Content-Type: application/json

{
    "result": {
        "info": [
            {
                "message": "Operation succeed without warning or error!"
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            }
        ]
    }
}
```

Equivalent Curl Command

```
COMMAND

curl -i -u hv5uaqOWF5kuISVnUiGEabOL8fsczsK98zVwpHYWgKE=: -X POST
https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user -H 'Content-Type:
application/json' -d '{"change-password-at-signin": "false", "console-
access": "false", "enabled": "true", "fullname": "user0001", "one-time-
use": "false", "password-cleartext": "abc123", "username": "user0002"}'

RESPONSE

HTTP/1.1 201 CREATED

Content-Type: application/json

Content-Length: 128


{
  "result": {
    "warnings": [
      {
        "message": "The configuration has been implicitly changed"
      }
    ]
  }
}
```

PUT API Call: Update Full name field of Specific user

```
REQUEST

PUT /api/v1/configuration/authentication/auth-servers/auth-server/Sys-
Local/local/users/user/user0001/fullname HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
cDkvaDg1eXRFbWtEenZrR1NtUTR6NzdwNllhN2FMSUM0MnZoMEY5Q0dhUT06

Content-Type: application/json

Cache-Control: no-cache

{

  "fullname":"REST API test for user0001"
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 122
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or error!"
      }
    ]
  }
}
```

Equivalent Curl Command

COMMAND

```
curl -i -u hv5uaqOWF5kuISVnUiGEabOL8fsczsK98zVwpHYWgKE=: -X PUT
https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user/user0001/fullname -H 'Content-
Type: application/json' -d '{"fullname": "user0001"}'
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 124
{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

After updating, fetch the User details and observe the fullname field updated:

```
REQUEST

GET /api/v1/configuration/authentication/auth-servers/auth-server/Sys-
Local/local/users/user/user0001 HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
cDkvaDg1eXRFbWtEenZrR1NtUTR6NzdwNllhN2FMSUM0MnZoMEY5Q0dhUT06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length →327

Content-Type →application/json

{

  "change-password-at-signin": "false",

  "console-access": "false",

  "enabled": "true",

  "fullname": "REST API test for user0001",

  "one-time-use": "false",

  "password-encrypted":
"3u+UR6n8AgABAAAATjgR31G4neKag2hxI+wjaNsRRZGD6wMQVkLEQv+DPQZdUrQi5IWPuihJ
f8tnrsBV0XCQly6WgZ79Jv1fyzmssg==",

  "username": "user0001"

}
```

DELETE API Call: DELETE Specific User

```
REQUEST

DELETE /api/v1/configuration/authentication/auth-servers/auth-server/Sys-
Local/local/users/user/user0001 HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
cDkvaDg1eXRFbWtEenZrR1NtUTR6NzdwNllhN2FMSUM0MnZoMEY5Q0dhUT06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length →122

Content-Type →application/json

{
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
  "result": {
    "info": [
      {
        "message": "Operation succeed without warning or error!"
      }
    ]
  }
}
```

Equivalent Curl Command

```
COMMAND

curl -i -u hv5uaqOWF5kuISVnUiGEabOL8fsczsK98zVwpHYWgKE=: -X DELETE
https://<hostname>/api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user/user0002/

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Type: application/json

Content-Length: 0
```

After deleting, try to fetch the resource and you would observe 404 response.

```
REQUEST

GET /api/v1/configuration/authentication/auth-servers/auth-
server/Sys-Local/local/users/user/user0001 HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
cDkvaDg1eXRFbWtEenZrR1NtUTR6NzdwNllhN2FMSUM0MnZoMEY5Q0dhUT06

Content-Type: application/json

Cache-Control: no-cache

RESPONSE

404 NOT FOUND

Content-Length: 105

Content-Type: application/json

{
  "result": {
    "errors": [
      {
        "message": "Resource does not exist."
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
      }
    ]
  }
}
```

Representing Configuration Resources Using Links

When performing a GET request on a configuration resource, the json response may have "href" attributes to represent smaller resources within.

As an example, `"GET /api/v1/configuration"` returns:

```
{
  "users": {
    "href": "/api/v1/configuration/users"
  },
  "system": {
    "href": "/api/v1/configuration/system"
  },
  "authentication": {
    "href": "/api/v1/configuration/authentication"
  },
  "administrators": {
    "href": "/api/v1/configuration/administrators"
  }
}
```

The href values can be used to access smaller resources.

© 2020 by Pulse Secure, LLC. All rights reserved

Sample GET/POST/PUT/DELETE Request and Responses in PPS

Below is a sample of GET/POST/PUT/DELETE request and responses:

GET API Call: Fetch the Details under Endpoint Policy

This example shows how to fetch the details under endpoint policy in PPS.

```
REQUEST
GET /api/v1/configuration/uac HTTP/1.1

Host xx.xx.xx.xx

Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06

Content-Type: application/json

{
    "admissionControl": {
        "href": "/api/v1/configuration/uac/admissionControl"
    },
    "host-enforcer": {
        "href": "/api/v1/configuration/uac/host-enforcer"
    },
    "infranet-enforcer": {
        "href": "/api/v1/configuration/uac/infranet-enforcer"
    },
    "mac-address-realms": {
        "href": "/api/v1/configuration/uac/mac-address-realms"
    },
    "network-access": {
        "href": "/api/v1/configuration/uac/network-access"
    },
    "snmpEnforcement": {
        "href": "/api/v1/configuration/uac/snmpEnforcement"
    }
}
RESPONSE
HTTP/1.1 200 OK

Content-Length: 340

Content-Type: application/json
```

Equivalent Curl Command

```
COMMAND

curl -i -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X GET
https://<hostname>/api/v1/configuration/uac

RESPONSE

HTTP/1.1 200 OK

Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Content-Length: 620
{
  "admissionControl": {
    "href": "/api/v1/configuration/uac/admissionControl"
  },
  "host-enforcer": {
    "href": "/api/v1/configuration/uac/host-enforcer"
  },
  "infranet-enforcer": {
    "href": "/api/v1/configuration/uac/infranet-enforcer"
  },
  "mac-address-realms": {
    "href": "/api/v1/configuration/uac/mac-address-realms"
  },
  "network-access": {
    "href": "/api/v1/configuration/uac/network-access"
  },
  "networkDeviceAdministration": {
    "href": "/api/v1/configuration/uac/networkDeviceAdministration"
  },
  "snmpEnforcement": {
    "href": "/api/v1/configuration/uac/snmpEnforcement"
  }
```

POST API Call: Create an SRX Enforcer in Infranet Enforcer Connection

This example shows how to create an SRX Enforcer in Infranet Enforcer connection.

```
REQUEST
POST /api/v1/configuration/uac/infranet-enforcer/connections/infranet-
enforcer/ HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "idp-for-local-sessions-only": "true",
    "junos": {
        "location-group": "- No 802.1X -",
        "password-encrypted":
"3u+UR6n8AgABAAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
    },
    "name": "SRX",
    "serial-number": [
        "SJFIOQJI4KNM"
    ],
    "severity-filter": "medium",
    "use-idp": "false"
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
}
```

RESPONSE

```
HTTP/1.1 201 OK
Content-Length: 122
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeed without warning or
error!"
            }
        ]
    }
}
```

Equivalent Curl Command

COMMAND

```
curl -i -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X POST
https://<hostname>/api/v1/configuration/uac/infranet-
enforcer/connections/infranet-enforcer -H 'Content-Type:
application/json' -d '{"idp-for-local-sessions-only": "true", "junos": {
"location-group": "- No 802.1X -", "password-
encrypted":"3u+UR6n8AgABAAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
},"name": "SRX","serial-number": ["SJFIOQJI4KNM"],"severity-filter":
"medium", "use-idp": "false"}'
```

RESPONSE

```
HTTP/1.1 201 CREATED


Content-Type: application/json
Content-Length: 124


{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

PUT API Call: Update Existing Configuration Where In Initial Location Group is Configured as Guest

This example updates the existing configuration where in the initial Location Group is configured as "Guest" and then later updated to "Default" Location group.

Before Updating the Location Group

```
REQUEST
GET api/v1/configuration/uac/network-access/radius-clients/radius-client/Radius%20Client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "location-group": "Guest",
    "name": "Radius Client",

}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 122
Content-Type: application/json
```

Equivalent Curl Command

```
COMMAND

curl -i -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X PUT https://<hostname>/api/v1/configuration/uac/network-access/radius-clients/radius-client/Radius%20Client -H 'Content-Type: application/json' -d '{"location-group": "Default","name": "Radius Client"}'

RESPONSE

HTTP/1.1 200 OK

Content-Type: application/json

Content-Length: 124

{
  "result": {
    "info": [
      {
        "message": "Operation succeeded without warning or error!"
      }
    ]
  }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

After Updating the Location Group

```
REQUEST
PUT api/v1/configuration/uac/network-access/radius-clients/radius-
client/Radius%20Client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{

    "location-group": "Default",

    "name": "Radius Client",

}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 122
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeed without warning or
error!"
            }
        ]
    }
}
```

DELETE API Call: Delete an SNMP Device

This example shows how to delete SNMP device from PPS.

```
REQUEST
DELETE api/v1/configuration/uac/snmpEnforcement/clients/client/ruckus
HTTP/1.1
Host 10.96.73.37
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
RESPONSE
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

Equivalent Curl Command

COMMAND

```
curl -I -u g4dncT4699c+IWip/+8urgXM0Luy1vQdj9zNxEFWEbM=: -X DELETE
https://<hostname>/api/v1/configuration/uac/snmpEnforcement/clients/clien
t/ruckus
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Type: application/json
Content-Length: 0
```

© 2020 by Pulse Secure, LLC. All rights reserved

PCS/PPS Configurations Using REST APIs

- Getting Active Sessions
- Getting Particular Active Session Details
- Deleting a Particular Active Session
- Deleting All Active Sessions
- Querying Set of Leased Licenses in the License Server System
- Pulling State from a License Server on a License Client
- Configuring Certificates based on CSR Workflow
- Creating a CSR for a Device Certificate
- Deleting Device Certificate by Its Subject Name
- Getting System Information
- Retrieving Serial Number and Machine ID
- Realm-based Administrator User Using Administrator Local Authentication Server
- Realm-based Administrator User Using AD Authentication Server
- Realm-based Administrator User Using LDAP Authentication Server
- Realm-based Administrator User Using Radius Authentication Server
- Realm-based Administrator User from a Particular Source IP
- Realm-based Administrator Authorization Role Mapping to .Administrator Role
- Specifying Session Validity for REST Admin Session
- Getting Active Directory Search Groups
- Adding Search Group to Active Directory
- Updating Active Directory Group
- Deleting Active Directory Groups
- Getting All LDAP Group List
- Adding Groups to LDAP
- Updating LDAP Source Group
- Deleting LDAP Source Group
- Creating a Cluster
- Adding a Member to Cluster
- Getting Cluster Status
- Deleting Cluster Member
- Getting Health Check Status
- Joining a Cluster
- VIP Failover
- Configuring IF MAP Server
- Configuring IF MAP Client
- Configuring No IF MAP Server
- Getting Config Without Pulse Packages (ESAP and Pulse Client Packages)
- Backing Up Binary Configuration
- Restoring Binary Configuration (import=normal)
- Restoring Binary Configuration (import=full)

© 2020 by Pulse Secure, LLC. All rights reserved

Getting Active Sessions

REQUEST

Fetch default number of active sessions (default=200)

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/system/active-users
```

Example :

```
curl -k -u K7Z7xA54AKnv1++kcViamCCiUrEBgMSP+sHKar4EcKY=:
https://10.209.125.4/api/v1/system/active-users
```

Fetch specified number of active sessions

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/system/active-
users?number=<number>
```

Example :

```
curl -k -u K7Z7xA54AKnv1++kcViamCCiUrEBgMSP+sHKar4EcKY=:
https://10.209.125.4/api/v1/system/active-users?number=250
```

RESPONSE

```
Content-Type: application/json
{
      "active-users": {
        "active-user-records": {
          "active-user-record": [
           {
             "active-user-name": "user1",
             "agent-type": "Windows 8.1 Google Chrome",
             "authentication-realm": "localrealm",
             "endpoint-security-status": "Not Applicable\nPassed
      Policies: \nFailed Policies: \nEliminated Roles: ",
             "events": 0,
             "login-node": "localhost2",
             "network-connect-ip": null,
             "network-connect-transport-mode": null,
             "session-id":
      "sidb03b1e971b7ebe163bb70c966a8ae2b50767aae300000000",
             "pulse-client-version": "9.1.4.1316",
             "user-roles": "localrealm",
             "user-sign-in-time": "2018/08/23 11:45:40"
           },
           {
             "active-user-name": "user2",
             "agent-type": "Windows 7 Google Chrome",
             "authentication-realm": "localrealm",
             "endpoint-security-status": "Not Applicable\nPassed
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
      Policies: \nFailed Policies: \nEliminated Roles: ",
             "events": 0,
             "login-node": "localhost2",
             "network-connect-ip": null,
             "network-connect-transport-mode": null,
             "session-id":
      "sid68377b6249d24784edfdd07edfe61ee9934b556100000000",
             "user-roles": "localrealm",
             "user-sign-in-time": "2018/08/23 11:46:15"
           }
          ]
        },
        "total-matched-record-number": 2,
        "total-returned-record-number": 2,
        "user-login-permission": true
      }
}
```

Getting Particular Active Session Details

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/system/active-
users?name=user2
```

Example:

```
curl -k -u K7Z7xA54AKnv1++kcViamCCiUrEBgMSP+sHKar4EcKY=:
https://10.209.125.4/api/v1/system/active-users?name=user2
```

RESPONSE

```
Content-Type: application/json
{
      "active-users": {
        "active-user-records": {
           "active-user-record": [
             {
               "active-user-name": "user2",
               "agent-type": "Windows 7 Google Chrome",
               "authentication-realm": "localrealm",
               "endpoint-security-status": "Not Applicable\nPassed
      Policies: \nFailed Policies: \nEliminated Roles: ",
               "events": 0,
               "login-node": "localhost2",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
                "network-connect-ip": null,
                "network-connect-transport-mode": null,
                "session-id":
      "sid68377b6249d24784edfdd07edfe61ee9934b556100000000",
                "user-roles": "localrealm",
                "user-sign-in-time": "2018/08/23 11:46:15"
              }
            ]
          },
          "total-matched-record-number": 1,
          "total-returned-record-number": 1,
          "user-login-permission": true
        }
}
```


Deleting a Particular Active Session

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/system/active-
users/session/sid6dc167193b66fef812ef3fdba62729e53f8499f0c25df3be -X DELETE
```

Example:

```
curl -k -u K7Z7xA54AKnv1++kcViamCCiUrEBgMSP+sHKar4EcKY=:
https://10.209.125.4/api/v1/system/active-
users/session/sid6dc167193b66fef812ef3fdba62729e53f8499f0c25df3be -X DELETE
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Deleting All Active Sessions

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/system/active-users?all -X
DELETE
```

Example:

```
curl -k -u K7Z7xA54AKnv1++kcViamCCiUrEBgMSP+sHKar4EcKY=:
https://10.209.125.4/api/v1/system/active-users?all -X DELETE
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Content-Length: 0
Content-Type: application/json
```

Querying Set of Leased Licenses in the License Server System

```
REQUEST
GET /api/v1/license/license-server-lease-information HTTP/1.1
Host: 10.209.114.226
Authorization: Basic
c2czWUJmc1lyUjcwN2daSFh6RHdqME1YSnNhdDZmcXlaOVZKNFNSdStaZz06
Content-Type: application/json
RESPONSE
HTTP/1.1 200 OK
Content-Length: 2210
Content-Type: application/json
{
      "leased-license-counts": {
         "features": {
            "feature": [
              {
                 "clients": {
                    "client-info": [
                       {
                           "leased-count": 0,
                           "name": "client1"
                       }
                     ]
                 },
                 "name": "Advanced Mobile License - Onboarding",
                 "total-count": 0
              },
              {
                 "clients": {
                 "client-info": [
                   {
                      "leased-count": 0,
                      "name": "client1"
                   }
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            ]
          },
           "name": "Cloud Secure feature",
           "total-count": 0
        },
        {
           "clients": {
             "client-info": [
               {
                  "leased-count": 0,
                  "name": "client1"
               }
             ]
           },
           "name": "Concurrent Meeting Users",
           "total-count": 0
         },
         {
           "clients": {
             "client-info": [
              {
                 "leased-count": 200,
                 "name": "client1"
              },
              {
                 "leased-count": 0,
                 "name": "client2"
              }
             ]
            },
            "name": "Concurrent Users",
            "total-count": 200
          },
          {
            "clients": {
              "client-info": [
                {
                  "leased-count": 0,
                  "name": "client1"
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
                    }
                  ]
                },
                "name": "Named Users",
                "total-count": 0
              },
              {
                "clients": {
                  "client-info": [
                    {
                      "leased-count": 0,
                      "name": "client1"
                    }
                  ]
                },
                "name": "Premier Java Remote Desktop Applet",
                "total-count": 0
              }
            ]
          },
          "machine-id": "VASPMVKIT1NJNFPPS",
          "query-summary": {},
          "release-info": {
          "build-number": "10124",
          "version": "9.0"
      },
          "serial-number": null,
          "signature":
      "HMx/W0VhDAABAAAApoB/uSUYcwJSlk7HeXVMXK6+KsIPTrJnjXrUci
      JEef2EKWyqgbDGoXhzYaGDl6Ye29oOw2KRQlyCM/HRpIpujA==",
          "time-stamp": "Fri Aug 24 14:43:00 2018"
      }
}
```


Pulling State from a License Server on a License Client

```
REQUEST
PUT /api/v1/license/license-client-lease-state HTTP/1.1
Host: 10.209.114.228
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Authorization: Basic
OWZBcVNKUkRCcEdjSEVQY3A0aDZ2UnFwdjhXbExIYzUxRS91TVU1VnBnMD06

Content-Type: application/json

{


}
```

Note: While using above URL (i.e., license-client-lease-state) by PUT operation, we provide empty JSON body as input, because PUT operation expects JSON body.

RESPONSE

```
HTTP/1.1 200 OK

Content-Length: 86

Content-Type: application/json

{
   "result": {
      "info": [
         {
           "message": "Success"
         }
      ]
   }
}
```

Configuring Certificates based on CSR Workflow

REQUEST

```
POST /api/v1/system/certificates/device-certificates HTTP/1.1

Host: 10.209.114.228

Authorization: Basic aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyaExubUcyVU5ibz06

Content-Type: application/json

{
         "cert":"MIINzgIBAzCCDYoGCSqGSIb3DQEHAaCCDXsEgg13MIINczCCBgQGCSqGSIb3DQE
         HAaCCBfUEggXxMIIF7TCCBekGCyqGSIb3DQEMCgECoIIE9jCCBPIwHAYKKoZIhvcNAQwBAz
         AOBAjpYgwUOJOweAICB9AEggTQFjak4T3ftSlkdoiOtc/xvhSfrrkezsl09tN6tqyuVYWFQ
         UZkpUIg4v2pU1zOvFOTPplnoVCmeiL2HX7OzuLPALcnSvGmaq61I+Y5dBWMmXMo+bs8sU36
         p6YS4D9Bq3VIMecAHwzc/30hPf+gaaoYSQiMuLa34CnNeFxPfxMlH0sXi1QeqaLAtMno5AM
         QW1/nHSAyJPwa5OWrJ5mkfHKh4kog893diYwo1mlIqlp7Qseza4+uosWAthih/jac1iDmlb
         03kjR+OQAukXFQ19ejvyrmMhcjhozARqwMgEj6I+JpdJPUxvwVytQ20Nj4lNDRnAb5sp1oA
         i0u5aN49afY6kRjNuKUeUkEmrpmumNJJufkDkKx1eqYOBOqQ50K1w9qFhEOaOLivGQa1Ijz
         Nyc+Bbs2TMw8RJWDsA7TVJhQKBcVjtIOSFzsVjyWJeI9VzB+iUbi+XCHYRQP0W6el6HWg2b
         31iNhMID5Lt2GWQOzT6iUVNlsZFoofyfXsZBY0JC6nsbvZVMRNBGXE2fEFA/qIga8Gn5E9z
         cIqibnXXW0jAOa+m3d+KRR49XaoAjgzpJ3ErqLVz1l/nGTix9W3H4mSHd9xX43h6Pbz0tGm
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
u6l9nnWP/52y6/TMQQB5v0RHe0klj+uX00ZuezmmeYEapX+SObQrMqmnvTgWApf7FzulcvA
IHomQ184MJzarNnhOpO1AQGESaa6tABtk2Yzpbm+g5SAgnjwxH0IjeF/kwapQttIYc1TM3q
Q9EsPKqbpaQna4qETIRLI3R6GVNTBnG/g9M9MQh2MtnvonSOlpjDs+TtLoO+BtY9J2XSMK0
wtXyONb67xjTRRsC1u1fAvP4RdyHpmM4JO3+VW1F4n8Vzl+RYrRj0sKja/jHm1ElZvhxJHb
wEMFDSvFIqAVfQGQKy1iJWSjalNeO2TEPVJOf2o+TofnYDq4hk0tABVdWLRfmn3byi91+xi
oIOLputEGG8ZtoAdlPkag/lKBnWa37z3eHnfQC9qWU8dcONBQo/HFxupj482jQa7lUg3fp7
apM4CuDQEgJWYNS4/Z+5+zEqq9q+/w9ke5Y/a/5ukeP9HRS3xpeEe56qb98qPx3dXSSDgXt
D1L6r48Dl+4ISYmLEl0yFwXtJ3vuYk5NiUjmZsuI1tnLQoxim5z6NUZ5/7G04mG/BzAX3qT
74MlRzVDa7uZdJPyJLyTGUtidn562HvYnrGtO9P+08OH6c2Dp4eOgNQCrhPP51ZHd9VNo0n
yqtZmZ0E4oHN4G7ud+6fwIvaSF9gpw1iTWAF5122dr1llAe3ZFPs5bzv7jrfY7LGuTh+l00
3MshmtYZAiw8nM1ODm4HstQsSxHWVb+WK4uiorvhq2cplJ+71rGQI/kCM8hdZJOUYzsrnQX
QUn/rS1O0w9VAP88SG9mJiQynoX4+BKYtnn4XE4D3tEFUygD2RmG2GdeGBjOeHh/KeMrXk2
z9oLEn7CaDeZQCp/7wGdDLfb/nAkmyiO6DWkPZzDAzGdSDd0gRTkY4LdtyjPTkeADN+wXvj
h6tutjgWgHEHI3xnvMan1/rzZV80SGpbqWFEcLCk158YuprYqVRN2CmJCILoVbUaay6Vq9j
aHkIkT3lxzU6UkNTKxqo3Rhad9StfxCRqlrYxgd8wEwYJKoZIhvcNAQkVMQYEBAEAAAAwXQ
YJKoZIhvcNAQkUMVAeTgBsAGUALQA2AGMANQA0AGUAMABjADQALQAyAGYANQBkAC0ANABjA
GYAMAAtAGEAYwBiAGUALQBhADAAYgBjAGUAZgA4AGIAYgA4AGEAMzBpBgkrBgEEAYI3EQEx
XB5aAE0AaQBjAHIAbwBzAG8AZgB0ACAAUgBTAEEAIABTAEMAaABhAG4AbgBlAGwAIABDAHI
AeQBwAHQAbwBnAHIAYQBwAGgAaQBjACAAUAByAG8AdgBpAGQAZQByMIIHZwYJKoZIhvcNAQ
cGoIIHWDCCB1QCAQAwggdNBgkqhkiG9w0BBwEwHAYKKoZIhvcNAQwBBjAOBAgQOOB7+SpCl
QICB9CAggcgKOhImrEmUqPOG8XR59tFV0HOdvnlfzxI7aM6PnAgwPiMSxa6e69kZ/DCeY5V
5XZkfW+nYAZvgGuZw26oLgVz14T/j0Z3kYTKcn1Mx+gvj5coadwfR21HirvwyndeXKJ6w1Y
h4omK/x4891AFgvKizeeOewczIGmWCqQh81HUgiR8aAfLU2neKxcLoGOfhQnN5k/SSKsBTu
UBQ80zGiXh+48xS4CTzE8vEyDXyQqE09sqxoDtWTw7U5cV8qXwpgy+FSb4c/Y/RCggTqmCL
+NwSMCvhEGfKSq9ZwJvniEpsQ1mHzK/e4ZRQH/C+eNCccV/6zR5onNbZ0fpVTGDCCG0Z970
5zzGur5z83CGy53fcHS2fdoQP6kqps7VeKbym2NBBT6tx9ZD4Ue988EQwkM0dw/7/9resv6
VnL+T9prJJq7pEPKyl8ocTSTPbINsSJ8f6z+R01/cxOnpyZ3pe2kWneC0xVUeTCsfip5DEb
OfgaCy4omJstlx57Z5GQrVfsO1V21NjY6i0Ev7e2AGyn+Kq2ZcrTBzijQpoA0djljaFodkB
VPwROkXCEjScfV/YjURTSgVcv1F1k/OyVf3EDcTXzjtOEuvkLrYsBANzAtcchE7tMlJdVlD
v4lA5nudd1plgQkwp911LOM5AieKMGuaSFLCq0RNTho61AFTeEOCgK1uDoRtac+TtgzrAyQ
GpUwQ/j/CFzy2yhQzSg2+nOFDA4D2I2Bw3SyMVAw45NtPPYnoplY9j0iRPfSOUzbHqULI8P
vRyICY3EhIv7MVzG812TMD1WOvZzaNonSB4plj+rq+aL6YHl5O3/AQ5v/n3b/ebrKDSSTYR
OC1nVfxxwF+nLTMeCPumAfb8JWdAmOvsUmyd8j8b6CgE2fMsR6yzZMmTcdispYe1r+at4hd
7v57K2JKcTKffS23zU9QZ6w30+soSr4dKhXVKoFny8pGZkgA5Dd5ksytKJgKJHM5Z6yRij8
cc0WwPrqK9jZvFxq0+t8rAFUA1QRbM6nnwF4g6z2vMdEtUYtnNXIZIWe5E6YJ1mxzn26dFA
t2AnM8MelPSNVaxVqhoCZAZOdRmhYXg4uT+4rMazBXJ7txtCNsQd/sW4WpOp9jzRoANfhxK
2uKkfRS62216u6hCoVCMj5D7UjB/4S80NZIwa67cikY/89t4vEZbwvS0dLQ2CMiQVeeUFTo
4Hq32RaVRPhIJql0MH/fyMIvSfqEoMUnY/D/26rKnivVp9XZdyd2ZKMV5nNFtbwC6UhhQ76
PwKRg5GsOuDjUxHzy0DXIgTcSuZWUeuDNM0iyVZ2LVCRPyTWAiur0nepcn1nVcehlxddqGS
u1AWSqmOODMmwymtm6mDKAvLnN8qjpL742bTIHkmxtUvoNxrgT4i+0jwGWlGNy6sx3JAXIY
Zv85xt+cV5KDvmF822w6CtUs5l8lWvBdAC6WD+wmnQzGsqvSbj9jLLKFxOtLYs863dDDtEN
dZIytrCKjEKNloY8X0flN1fczguZ8ssBa6XWQ4hjgwanpjBsvReJZcWogUFqYuXtZUB/mIU
SZyNSIFwCO4cWa4vqE4P1Pjl56jnIdpqwgqaljHTm7WsCEIbgdBfyJp75/vJR/A4PAJcsZm
FfIayNwM/zePFhZp0Udxrnoptzfsf4XspgZEPbHyxmfQG7f8sfAQq0iQlH0kpaBD3VuTrud
gOfFbVfrjim8UXUNhKpYSgy3GWeHXadrOHsOZ0Yj0a/AY5Wwny7RJAZO00UCMLGRVFxYjj9
RQvCPphejNVmhLNqlT3dqEczH3TptR4xILuoXC6sQkViBhV7dEp0nVzA6jUzCGOnYmCWi7/
N6+bD1XHC6dg76igIUHHiJz0jqHfIoxqAak+72Iv706QtVMyI+Cpe4FLRqhoNUJpHAT7+5E
Oq2WqWXB+KXk5/Wh7/CIo6pZsAuEAU0elDDz/mex2oUfigYvtywFPBo0fWzTqkWvP7Pl8E5
wudKl9Q+JYoNZVaapChTDJF9/OoVE1g0rrQ5nxzKQRrTbtekZSJ5j66p107ux2R+Q7MpRsm
wT8ERgW8CexPHOAIKAWSBpWaT6ogh1MletHIK++ShXSIRa3NbDjrwkU8q0E9wlCUyAfXnQv
4pTQaGHadF/j2F2foMBAW2Jgh1KP9UgB54K+KLRjoIFcEUqqh+j42bh2/c0jAppJtWNgn2j
FQzuK2I3E0MVVNOEPJmEvpDXM1DZZhFNxeL8D+LfMn1B4zNTdngE0arUOspr72Rm0Rx43Oc
U0w/nkL6DckhvIZdco4PSLLXJeBW/fBc2Ws04/qxEKwreGwCr3fM17X4HZtCRJOsVj0Bg6J
Ap3f30Os55bjQanFubM9YFZrC6rGnKshyiUIFutMPwzbuIWCWQP29TnlSJWk91C0jb2oy6/
2O9o7U78grLvGllSyynqehN8TLxP9MDswHzAHBgUrDgMCGgQU9XDxDBt/loGEHzU/DE0xAa
6823YEFFmEIfAiPtILVXcDNuDn0rU1xc24AgIH0A==",

"password": <certifcicate_password>,

"internal-interfaces": { "internal-interface" : ["<Internal Port>",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        "vport1"] },
        "external-interfaces": { "external-interface" : ["<External Port>"] },
        "management-interface": true
}
RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 112
Content-Type: application/json
{
      "result": {
       "info": [
         {
           "message": "Operation successfully completed."
         }
       ]
      }
}
```

Creating a CSR for a Device Certificate

```
REQUEST
POST /api/v1/system/certificates/device-certificate-csrs HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyaExubUcyVU5ibz06
Content-Type: application/json
{
      "subject-common-name": "QA.pcs.company.com",
      "key-type": "ECDSA",
      "ecc-curve": "P-384"
}
RESPONSE
HTTP/1.1 201 OK
Content-Length: 266
Content-Type: application/json
{
      "result": {
         "info": [
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
          {
             "message": "Created CSR 'CSR_164' successfully"
          },
          {
             "message": "Use POST
      /api/v1/system/certificates/device-certificate-
      csrs/CSR_164/certificate to upload the signed certificate"
          }
       ]
      }
}
```

Deleting Device Certificate by Its Subject Name

```
REQUEST

DELETE /api/v1/system/certificates/device-
certificates/srikrsa.test.saqacertserv.com HTTP/1.1

Host: 10.209.114.228

Authorization: Basic
aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyaExubUcyVU5ibz06

Content-Type: application/json

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json
```

Getting System Information

```
REQUEST

GET /api/v1/system/system-information HTTP/1.1

Host: 10.209.114.228

Authorization: Basic
aWZuM2VmZVZTRU9YNVZkVVZ3eFpiYWdob3VCTndxZEkyaExubUcyVU5ibz06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length: 193

Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
{
      "rollback-partition-information": {
         "build": "2330",
         "os-name": "ive-sa",
         "os-version": "9.1R2"
      },
      "software-inventory": {
         "software": {
           "build": "4520",
           "name": "IVE-OS",
           "type": "operating-system",
           "version": "9.1R4"
         }
      },
      "system-information": {
         "hardware-model": "PSA5000-V",
         "host-name": "localhost2",
         "os-name": "ive-sa",
         "os-version": "9.1R4",
         "serial-number": "VASPHJPEG824R1U0S"
      }
}
```


Retrieving Serial Number and Machine ID

REQUEST

```
GET /api/v1/system/system-information HTTP/1.1
Host: 10.96.116.30
Authorization: Basic
czM3MzVDTFVYbnFObFR5NHdNSTFES3piSDhrMTVwR0pLV2gwOTlMYmxhYz06
Content-Type: application/json
```

RESPONSE


```
HTTP/1.1 200 OK
Content-Length: 193
Content-Type: application/json
{
  "rollback-partition-information": {
    "build": "5801",
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
    "os-name": "ive-sa",
    "os-version": "9.1R6"
  },
  "software-inventory": {
    "software": {
      "build": "6087",
      "name": "IVE-OS",
      "type": "operating-system",
      "version": "9.1R7"
    }
  },
  "system-information": {
    "cluster-node": {},
    "hardware-model": "PSA-3000",
    "host-name": "node1",
    "machine-id": "0312MB24A0EZ504VS",
    "os-name": "ive-sa",
    "os-version": "9.1R7",
    "serial-number": "0312022017100103"
  }
}
```

Realm-based Administrator User Using Administrator Local Authentication Server

```
REQUEST
POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.228
Authorization: Basic YWRtaW4xOmRhbmExMjM=
Content-Type: application/json
{
      “realm”: “<realm-name>”
}
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
      "api_key": "MjUwOGQyNzAyOWU3MWQ2MzNiMTM2Njg2MzAwNDg3MjU="
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Realm-based Administrator User Using AD Authentication Server

```
REQUEST
POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.228
Authorization: Basic bmF6ZWVyOlBzZWN1cmUxMjMk
Content-Type: application/json
{
      "realm": "AdminADRealm"
}
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
      "api_key": "ODRjOTcxOTY5ZTlmYTcwY2QwYzk1ZDBjMWQ5N2RmN2Q="
}
```

Realm-based Administrator User Using LDAP Authentication Server

```
REQUEST
POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.228
Authorization: Basic bmF6ZWVyOlBzZWN1cmUxMjMk
Content-Type: application/json
{
     "realm": "LDAPRealm"
}
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
      "api_key": "ZTQxNTIxOTJhNmUwMjg3MWI5MjZkYmE1MGM0MzdiMDI="
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Realm-based Administrator User Using Radius Authentication Server

```
REQUEST
POST /api/v1/realm_auth HTTP/1.1
Host: 10.209.114.225
Authorization: Basic amFjazpqdW5pcGVy
Content-Type: application/json
{
      "realm": "RadiusAdminRealm"
}
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
      "api_key": "MGMzZjJkZDZlYmRlYzg0MDE5NzkwYzE1ZGM5MmQyYTQ="
}
```

Realm-based Administrator User from a Particular Source IP

```
REQUEST
PUT /api/v1/configuration/administrators/admin-
realms/realm/AdminLocalAuthRealm/authentication-policy/source-
ip/customized HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
T1dFM056VTBPVEl5T0dFeU16WXpOakU0WVRFek9EWXhOamRoTVdVNFpqYz06
Content-Type: application/json
{
      "customized": "selected-ip"
}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 124
Content-Type →application/json
{
      "result": {
         "info": [
           {
              "message": "Operation succeeded without warning or
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
      error!"
           }
       ]
      }
}
REQUEST
POST /api/v1/configuration/administrators/admin-
realms/realm/AdminLocalAuthRealm/authentication-policy/source-
ip/ips/ip HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
T1dFM056VTBPVEl5T0dFeU16WXpOakU0WVRFek9EWXhOamRoTVdVNFpqYz06
Content-Type: application/json
{
   "access": "allow",
   "address": "10.96.158.3",
   "netmask": "255.255.255.255"
}
RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 124
Content-Type: application/json
{
      "result": {
        "info": [
         {
           "message": "Operation succeeded without warning or
      error!"
         }
       ]
      }
}
```

Realm-based Administrator Authorization Role Mapping to .Administrator Role

```
REQUEST
PUT /api/v1/configuration/administrators/admin-
realms/realm/AdminADRealm/role-mapping-rules HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
TldVNFl6TmtOVEZqTkRFek1EUXdPVGRoTlRrMk9UWTBaR0l3TkRnM1ptST06
Content-Type: application/json
{
      "user-selects-role": "false",
      "rule": [
        {
           "roles": [
            ".Administrators"
           ],
           "stop-rules-processing": "true",
           "group": {
             "group-names": [
                "PCS-QA/systems"
             ]
           },
           "name": "AdminADRoleMapping"
        }
      ],
      "user-selects-roleset": "false"
}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
      "result": {
        "info": [
          {
            "message": "Operation succeeded without warning or
      error!"
          }
        ]
      }
}
```

Specifying Session Validity for REST Admin Session

```
REQUEST
PUT /api/v1/configuration/administrators/admin-roles/admin-
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
role/%2EAdministrators/general/session-options HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
TldVNFl6TmtOVEZqTkRFek1EUXdPVGRoTlRrMk9UWTBaR0l3TkRnM1ptST06
Content-Type: application/json
{
    "idle-timeout": "5"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
          "result": {
              "info": [
                  {
                      "message": "Operation succeeded without
     warning or error!"
                  }
              ]
          }
}
```

Getting Active Directory Search Groups

REQUEST

```
GET /api/v1/configuration/authentication/auth-servers/auth-
server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 294
Content-Type: application/json
{
      "ad-group": [
       {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        "group": "PCS-QA/core",
        "name": "PCS-QA/core",
        "sid": "S-1-5-21-3875260349-1888520165-453808128-1112"
      },
      {
        "group": "PCS-QA/systems",
        "name": "PCS-QA/systems",
        "sid": "S-1-5-21-3875260349-1888520165-453808128-1108"
      }
    ]
}
```

Adding Search Group to Active Directory

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-
server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
      "ad-group": [
         {
             "group": "PCS-QA/systems",
             "name": "PCS-QA/systems"
         },
         {
             "group": "PCS-QA/core",
             "name": "PCS-QA/core"
         }
      ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
   "result": {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
      "info": [
       {
         "message": "Operation succeeded without warning or error!"
       }
      ]
   }
}
```

Updating Active Directory Group

NOTE: To update a group, first get already available list using GET operation and append new group to it before PUT.

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-
server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
      "ad-group": [
        {
           "group": "PCS-QA/core",
           "name": "PCS-QA/core",
           "sid": "S-1-5-21-3875260349-1888520165-453808128-1112"
        },
        {
           "group": "PCS-QA/systems",
           "name": "PCS-QA/systems",
           "sid": "S-1-5-21-3875260349-1888520165-453808128-1108"
        },
        {
           "group": "PCS-QA/client",
           "name": "PCS-QA/client",
           "sid": "S-1-5-21-3875260349-1888520165-453808128-1113"
        }
      ]
}
```

RESPONSE

© 2020 by Pulse Secure, LLC. All rights reserved

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
      "result": {
         "info": [
          {
            "message": "Operation succeeded without warning or
         error!"
          }
         ]
    }
}
```

Deleting Active Directory Groups

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-
server/ADServer/ad/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
      "ad-group": [
      ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
      "result": {
         "info": [
           {
             "message": "Operation succeeded without warning or
         error!"
           }
         ]
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
    }
}
```

Getting All LDAP Group List

```
REQUEST

GET /api/v1/configuration/authentication/auth-servers/auth-
server/LDAPServer/ldap/server-catalog/groups HTTP/1.1

Host: 10.209.116.192

Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06

Content-Type: application/json
```

Adding Groups to LDAP

```
REQUEST

PUT /api/v1/configuration/authentication/auth-servers/auth-
server/LDAPServer/ldap/server-catalog/groups HTTP/1.1

Host: 10.209.116.192

Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06

Content-Type: application/json

{
      "user-group": [
        {
          "dn": "CN=Administrators,CN=Builtin,DC=pcs-
      qa,DC=blrlab,DC=net",
          "group-type": "static",
          "name": "Administrators"
        },
        {
          "dn": "CN=Users,CN=Builtin,DC=pcs-qa,DC=blrlab,DC=net",
          "group-type": "static",
          "name": "Users"
        }
      ]
}

RESPONSE

HTTP/1.1 200 OK

Content-Length: 124
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Content-Type: application/json
{
      "result": {
         "info": [
           {
             "message": "Operation succeeded without warning or
         error!"
           }
         ]
     }
}
```

Updating LDAP Source Group

NOTE: To update a group, first get already available list using GET operation and append new group to it and then perform PUT operation.

```
REQUEST

PUT /api/v1/configuration/authentication/auth-servers/auth-
server/LDAPServer/ldap/server-catalog/groups HTTP/1.1

Host: 10.209.116.192

Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06

Content-Type: application/json

{
      "user-group": [
        {
          "dn": "CN=Administrators,CN=Builtin,DC=pcs-
      qa,DC=blrlab,DC=net",
          "group-type": "static",
          "name": "Administrators"
        },
        {
          "dn": "CN=Users,CN=Builtin,DC=pcs-qa,DC=blrlab,DC=net",
          "group-type": "static",
          "name": "Users"
        },
        {
          "dn": "CN=Guests,CN=Builtin,DC=pcs-qa,DC=blrlab,DC=net",
          "group-type": "static",
          "name": "Guests"
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        }
    ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
      "result": {
         "info": [
           {
             "message": "Operation succeeded without warning or
         error!"
           }
         ]
    }
}
```

Deleting LDAP Source Group

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-
server/LDAPServer/ldap/server-catalog/groups HTTP/1.1
Host: 10.209.116.192
Authorization: Basic
RU9jaHYwdmlqVnJibDBqeE9obTlYZDVOdHhVS2FMeSttVzBqL1pKUXh6bz06
Content-Type: application/json
{
      "user-group": [
      ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 124
Content-Type: application/json
{
      "result": {
         "info": [
           {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            "message": "Operation succeeded without warning or
        error!"
          }
        ]
    }
}
```

Creating a Cluster

REQUEST

```
PUT /api/v1/cluster HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
TldVNFl6TmtOVEZqTkRFek1EUXdPVGRoTlRrMk9UWTBaR0l3TkRnM1ptST06
Content-Type: application/json
{
    "cluster-name": "cluster1",
    "cluster-password": "dana123",
    "member-name": "nodeA",
    "action": "create"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 118
Content-Type: application/json
{
          "result": {
              "info": [
                  {
                      "message": "Created cluster
      'cluster1' successfully"
                  }
              ]
          }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Adding a Member to Cluster

```
REQUEST

POST /api/v1/cluster/members HTTP/1.1

Host: 10.209.116.214

Authorization: Basic
THI5bmxreU50UE04MWJ6OHRhbjhFMW1PYTVuV3V5MG5XN0oyNmNWcTRhbz06

Content-Type: application/json

{
   "member-name" : "node225",
   "member-ip" : "3.209.114.225",
   "member-netmask" : "255.0.0.0",
   "member-gateway" : "3.0.0.1",
   "member-external-ip" : "2.209.114.225",
   "member-external-netmask" : "255.0.0.0",
   "member-external-gateway" : "2.0.0.1"
}

RESPONSE

HTTP/1.1 200 OK

Content-Length: 125

Content-Type: application/json

{
  "result": {
    "info": [
      {
        "message": "Added member 'node225' to cluster
successfully"
      }
    ]
  }
}
```

Getting Cluster Status

```
REQUEST

GET /api/v1/cluster HTTP/1.1

Host: 10.209.114.228

Authorization: Basic
TWN2cUEzbFRYQXcySjBSbGpKWTAzdk1oa2RiTDFLUVJDUjNNdlQ0UlRJdz06
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Content-Type: application/json
RESPONSE
HTTP/1.1 200 OK
Content-Length: 619
Content-Type: application/json
{
      "members": [
          {
              "enabled": true,
              "external-ip": "",
              "external-network": "",
              "internal-ip": "3.209.114.225",
              "internal-netmask": "255.0.0.0",
              "name": "node225",
              "notes": "Enabled, Unreachable",
              "status-code": "0x18"
          },
          {
              "enabled": true,
              "external-ip": "10.209.114.194",
              "external-network": "255.255.240.0",
              "internal-ip": "3.209.114.228",
              "internal-netmask": "255.0.0.0",
              "name": "nodeA",
              "notes": "Leader",
              "status-code": "0x19004"
          }
          ],
          "mode": "Active/Active",
          "name": "cluster1"
}
{
         "external-vip-ipv4": "10.204.56.76",
         "external-vip-owner": "node-51-39",
         "internal-vip-ipv4": "10.204.56.75",
         "internal-vip-owner": "node-51-39",
         "members": [
           {
             "enabled": true,
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            "external-ip": "10.204.56.82",
            "external-netmask": "255.255.240.0",
            "internal-ip": "10.204.51.39",
            "internal-netmask": "255.255.240.0",
            "name": "node-51-39",
            "notes": "Leader",
            "status-code": "0x1b004"
          },
          {
            "enabled": true,
            "external-ip": "10.204.56.87",
            "external-netmask": "255.255.240.0",
            "internal-ip": "10.204.56.88",
            "internal-netmask": "255.255.240.0",
            "name": "Node-something",
            "notes": "Enabled, Unreachable",
            "status-code": "0x18"
          }
        ],
        "mode": "Active/Passive",
        "name": "TEST-CLUSTER"
}
```


Deleting Cluster Member

REQUEST

```
DELETE /api/v1/cluster/members/node225 HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
TWN2cUEzbFRYQXcySjBSbGpKWTAzdk1oa2RiTDFLUVJDUjNNdlQ0UlRJdz06
Content-Type: application/json
```

RESPONSE


```
HTTP/1.1 200 OK
Content-Length: 129
Content-Type: application/json
{
          "result": {
              "info": [
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
                {
                    "message": "Removed member 'node225'
      from cluster successfully"
                }
            ]
        }
}
```

Getting Health Check Status

```
REQUEST
GET /api/v1/system/healthcheck
Host: 10.209.114.228
Content-Type: application/json
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
{
   "message": "Security Gateway is accessible."
}

REQUEST
GET /api/v1/system/healthcheck?status=all HTTP/1.1
Host: 10.209.114.228
Content-Type: application/json
RESPONSE
Content-Type: application/json
{
    "CPU-UTILIZATION4": 8,
    "SSL-CONNECTION-COUNT": 0,
    "MAX-LICENSED-USERS-REACHED": "NO",
    "SWAP-UTILIZATION": 1,
    "DISK-UTILIZATION": -1,
    "USER-COUNT": 0,
    "VPN-TUNNEL-COUNT": 0
}

REQUEST
GET /api/v1/system/healthcheck?status=sbr HTTP/1.1
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Host: 10.209.114.228
Content-Type: application/json
RESPONSE
Content-Type: application/json
{
   "SBR-AVAILABLE": 1
}
```

Joining a Cluster

```
REQUEST
PUT /api/v1/cluster HTTP/1.1
Host: 10.209.114.228
Authorization: Basic
SkUyV1BaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
   "cluster-name": "cluster",
   "cluster-password": "dana123",
   "member-address": "3.209.114.225",
   "action": "join"
}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 116
Content-Type: application/json
{
   "result": {
     "info": [
       {
         "message": "Joined cluster 'cluster' successfully"
       }
     ]
   }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

VIP Failover

```
REQUEST

PUT /api/v1/cluster

Host: 10.209.114.228

Authorization: Basic
SkUyV1BaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06

Content-Type: application/json

{
   "action": "vip-failover"
}

RESPONSE

In case of active-passive cluster:

{
  "result": {
    "info": [
      {
        "message": "VIP fail-over initiated"
      }
    ]
  }
}

In case of active-active cluster:

{
  "result": {
    "info": [
      {
        "message": "Node not part of an Active-Passive cluster.
Invalid operation."
      }
    ]
  }
}
```

Configuring IF MAP Server

```
REQUEST

PUT /api/v1/configuration/system/ifmap/overview/ifmap-config/

Host: xx.xxx.xxx.xxx
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Authorization: Basic
SkUyV1BaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
      "ifmap-config": " server "
}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 116
Content-Type: application/json
{
    "result": {
       "info": [
          {
              "message": ": "Operation succeeded without warning or
error!"
          }
       ]
    }
}
```

Configuring IF MAP Client

```
REQUEST
PUT /api/v1/configuration/system/ifmap/overview/ifmap-config/
Host: xx.xxx.xxx.xxx
Authorization: Basic
SkUyV1BaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
"auth-type": "basic",
    "cert": "None",
    "ifmap-config": "client",
    "password-encrypted":
"3u+UR6n8AgABAAAAe9Px2XELrbvvAZACcoOJXBM105llgG8QQLNR4hcLNrE=",
    "server-url": "https://<PPS-IP-Address>/dana-ws/soap/dsifmap",
    "username": "admin1"
}
{
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
    "auth-type": "cert",
    "cert": "xx.xxx.xx.xx",
    "ifmap-config": "client",
    "password-encrypted":
"3u+UR6n8AgABAAAAe9Px2XELrbvvAZACcoOJXBM105llgG8QQLNR4hcLNrE=",
    "server-url": "https://<PPS-IP_Address>/dana-ws/soap/dsifmap",
    "username": "admin1"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 116
Content-Type: application/json
{
    "result": {
       "info": [
          {
              "message": ": "Operation succeeded without warning or
error!"
          }
       ]
    }
}
```

Configuring No IF MAP Server

REQUEST

```
PUT /api/v1/configuration/system/ifmap/overview/ifmap-config/
Host: xx.xxx.xxx.xxx
Authorization: Basic
SkUyV1BaVjRjcGxleElRMnNiZXpYajE2dEVIUm9Oa05WWDdRWHh3MmpJZz06
Content-Type: application/json
{
      "ifmap-config": "no-ifmap"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 116
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
{
    "result": {
       "info": [
          {
              "message": ": "Operation succeeded without warning or
error!"
          }
       ]
    }
}
```

Getting Config Without Pulse Packages (ESAP and Pulse Client Packages)

```
REQUEST

GET /api/v1/configuration/authentication/endpoint/host-
checker/esaps?expand&&excludePulsePackages HTTP/1.1

Host: 10.209.125.139

Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length: 561

Content-Type: application/json

{
      "active-version": "3.3.5",
         "default-version": "3.3.5",
         "esap": [
           {
               "esap-version": "3.3.5",
               "last-activated-time": "Sun 17 Mar 2019 23:54:12
         PDT",
               "upload-time": "Sun 17 Mar 2019 23:53:35 PDT"
           },
           {
              "esap-version": "3.3.6",
              "last-activated-time": "Never",
              "upload-time": "Mon 18 Mar 2019 21:45:31 PDT"
           },
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            {
               "esap-version": "3.3.7",
               "last-activated-time": "Never",
               "upload-time": "Mon 18 Mar 2019 21:46:12 PDT"
            }
         ],
         "force-same-esap": "false",
         "opswat-sdk-version": "4"
}
```

Backing Up Binary Configuration

```
REQUEST

GET /api/v1/system/binary-configuration HTTP/1.1

Host: 10.204.51.39

Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06

RESPONSE

HTTP/1.1 200 OK

Content-Type: text/html; charset=utf-8

Content-Length: 50753630

UEsDBBQAAAAIAE9VmU4J1asqz3cDAKx3AwAKABwAc3lzdGVtLmNmZ1VUCQADvUHB

XL1BwVx1eAsAAQQAAAAABAAAAAAAC4D0fwnTMa1OLV2XgACOdwMAINEfP2AuIVXV

B1FhtptLC259gyNPT7WwhtQKbp2Y2+d1h1MTflQis8wbHytXP19D+SM+amX5UKeO

GDUggxgbrEQMXmwOSv8YBrvXIBShmGO5BVqfUemvdNK3OB+S/g8+LIPG5i2c3LVm

W8hY3PLQ9CJHMrFSBFtgyTX2at85MGCsupxd2gOQQ9e138KrI2hBoywDzCJiRUSU

...
```

Restoring Binary Configuration (import=normal)

The import normal mode will import the binary configuration excluding the IP, network configurations and cluster configuration. The normal mode is similar to default option in binary import.

```
REQUEST

PUT /api/v1/system/binary-configuration?import=normal HTTP/1.1

Or

PUT /api/v1/system/binary-configuration HTTP/1.1

Host: 10.204.51.39

Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Content-Type: text/html; charset=utf-8
```

RESPONSE

```
HTTP/1.1 200 OK
{
  "result": {
    "info": [
      {
        "message": "Operation successfully completed."
      }
    ]
  }
}
Error Cases:
import mode specified is incorrect (other than normal or full)
Content-Length: 100
Content-Type: application/json
{
 "result": {
    "errors": [
      {
         "message": "Invalid import mode"
      }
    ]
  }
}
Content type is not a base 64 encoded binary configuration string
Content-Length: 126
Content-Type: application/json
{
 "result": {
   "errors": [
     {
       "message": "Error - Failed to extract configuration files"
     }
    ]
  }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Restoring Binary Configuration (import=full)

The import full mode will import everything from the binary configuration provided in the body. This is similar to full binary import.

```
REQUEST
PUT /api/v1/system/binary-configuration?import=full HTTP/1.1
Host: 10.204.51.39
Authorization: Basic
dS9UOURJRWswZzVyMTdieUJqVnhaQnExZUpTTW9ndCtIdGZzMnczMmlzRT06
Content-Type: text/html; charset=utf-8
Body data:
Base64 configuration string as received in GET request)

UEsDBBQAAAAIAE9VmU4J1asqz3cDAKx3AwAKABwAc3lzdGVtLmNmZ1VUCQADvUHB
XL1BwVx1eAsAAQQAAAAABAAAAAAAC4D0fwnTMa1OLV2XgACOdwMAINEfP2AuIVXV
B1FhtptLC259gyNPT7WwhtQKbp2Y2+d1h1MTflQis8wbHytXP19D+SM+amX5UKeO
GDUggxgbrEQMXmwOSv8YBrvXIBShmGO5BVqfUemvdNK3OB+S/g8+LIPG5i2c3LVm
……
RESPONSE
HTTP/1.1 200 OK
Content-Length: 112
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "Operation successfully completed."
      }
    ]
  }
}
Error Cases:
import mode specified is incorrect (other than normal or full)
Content-Length: 100
Content-Type: application/json
{
 "result": {
     "errors": [
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
       {
          "message": "Invalid import mode"
       }
     ]
  }
}
Content type is not a base 64 encoded binary configuration string
Content-Length: 126
Content-Type: application/json
{
 "result": {
    "errors": [
      {
        "message": "Error - Failed to extract configuration files"
      }
     ]
  }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

PCS-Specific Configurations Using REST APIs

- Creating a VLAN
- Deleting a VLAN
- Creating a User Role
- Fetching the User Login Statistics
- Updating the User Role Settings
- Deleting a User Role
- Creating a User Realm
- Deleting a User Realm
- Creating a Resource Profile
- Deleting a Resource Profile
- Creating a Resource Policy
- Fetching a Resource Policy
- Deleting a Resource Policy
- Creating an AD Authentication Server
- Deleting an AD Authentication Server
- Creating an LDAP Authentication Server
- Creating a Radius Server
- Modifying Radius Server Details
- Creating Sign-In-Policy
- Deleting Sign-In-Policy
- Disabling Sign-in-URL
- Creating a Web Bookmark for a Role
- Reordering
- Fetching the Resource with Multiple Identifiers
- Updating Resource Identified Using Multiple Identifiers
- Fetching Active Number of HTML5 Sessions
- Updating Password in Clear Text
- Applying Authcode and Downloading Licenses from PCLS on VA-SPE|PSA-V
- Applying License
- Deleting License
- Getting License Clients
- Getting License Report from License Server
- Enabling/Disabling ICE License
- Getting the Current Status of ICE License
- Exporting TOTP Users from One Device to Another Device
- Importing TOTP Users from One Device to Another Device
- Resetting TOTP User
- Unlocking TOTP User
- Sample Error Responses
- Limitations

© 2020 by Pulse Secure, LLC. All rights reserved

Creating a VLAN

To create a VLAN on a cluster node:

REQUEST

```
POST /api/v1/configuration/system/network/vlans/Node88/vlan/ HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

{

    "arp-cache": {

        "arp-entry": []

    },

    "name": "vlan-int-1",

    "routes": {

        "route": []

    },

    "settings": {

        "default-gateway": "2.0.0.1",

        "default-vlan-interface": "false",

        "enable-ipv6": "enabled",

        "ip-address": "2.2.2.2",

        "ipv6-address": "fc00:7777:5678:5678::222",

        "ipv6-default-gateway": "fc00:7777:5678:5678::3",

        "ipv6-prefix-length": "64",

        "is-enabled": "enabled",

        "netmask": "255.0.0.0",

        "vlan-id": "2",

        "vlan-parent": "0"

    },

    "virtual-ports": {

        "virtual-port": []

    }

}
```

RESPONSE

© 2020 by Pulse Secure, LLC. All rights reserved

```
HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
"result": {
"warnings": [
{
"message": "The configuration has been implicitly changed"
}
            ]
          }
}
```

Deleting a VLAN

To delete a VLAN from cluster node:

```
REQUEST

DELETE /api/v1/configuration/system/network/vlans/Node88/vlan/vlan-int-1
HTTP/1.1
Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
Content-Type: application/json

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json
```

Creating a User Role

To create a user role:

```
REQUEST

POST /api/v1/configuration/users/user-roles/user-role/ HTTP/1.1
Host: 10.209.113.88
Authorization: Basic
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

{
    "name": "rest-userrole-4",
    "web": {
        "web-bookmarks": {
            "bookmark": [
                {
                    "auto-allow": "disable",
                    "description": "",
                    "name": "web-bm-1",
                    "new-window": "false",
                    "no-address-bar": "false",
                    "no-tool-bar": "false",
                    "parent": "--none--",
                    "standard": {
                        "url": "http://www.msn.com"
                    }
                }
            ]
        },
        "web-options": {
            "browsing-untrusted-sslsites": "true",
            "flash-content": "false",
            "hpxproxy-connection-timeout": "1800",
            "http-connection-timeout": "240",
            "java-applets": "true",
            "mask-hostname": "false",
            "persistent-cookies": "false",
            "rewrite-file-urls": "false",
            "rewrite-links-pdf": "false",
            "unrewritten-page-newwindow": "false",
            "user-add-bookmarks": "false",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            "user-enter-url": "false",
            "users-bypass-warnings": "false",
            "warn-certificate-issues": "true",
            "websocket-connection-timeout": "900"
        }
    }
}
RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 122
Content-Type: application/json
         {
             "result": {
                 "info": [
                     {
                         "message": "Operation succeed without
   warning or error!"
                     }
                 ]
             }
         }
```

Fetching the User Login Statistics

To fetch the user login statistics:

```
REQUEST
GET /api/v1/system/user-stats HTTP/1.1
Host: 10.209.113.88
Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
Content-Type: application/json
RESPONSE
HTTP/1.1 200 OK
Content-Length: 169
Content-Type: application/json
{
         "user-stats": {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            "allocated-user-count": "25",
            "current-user-count": "0",
            "max-active-user-count-24hrs": "1",
            "min-active-user-count-24hrs": "0"
        }
}
```

Updating the User Role Settings

To update the user role settings:

```
REQUEST

PUT /api/v1/configuration/users/user-roles/user-role/rest-userrole-4
HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

{

    "name": "rest-userrole-4",

    "web": {

        "web-bookmarks": {

            "bookmark": [

                {

                    "auto-allow": "disable",

                    "description": "",

                    "name": "web-bm-1",

                    "new-window": "false",

                    "no-address-bar": "false",

                    "no-tool-bar": "false",

                    "parent": "--none--",

                    "standard": {

                        "url": "http://www.yahoo.com"

                    }

                }

            ]
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        },
        "web-options": {
            "browsing-untrusted-sslsites": "true",
            "flash-content": "false",
            "hpxproxy-connection-timeout": "1800",
            "http-connection-timeout": "240",
            "java-applets": "true",
            "mask-hostname": "false",
            "persistent-cookies": "false",
            "rewrite-file-urls": "false",
            "rewrite-links-pdf": "false",
            "unrewritten-page-newwindow": "false",
            "user-add-bookmarks": "false",
            "user-enter-url": "false",
            "users-bypass-warnings": "false",
            "warn-certificate-issues": "true",
            "websocket-connection-timeout": "900"
        }
    }
}
        }
    }
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 122
Content-Type: application/json
{
         "result": {
            "info": [
              {
                "message": "Operation succeed without warning or
   error!"
              }
            ]
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
          }
}
```

Deleting a User Role

To delete a user role:

```
REQUEST

DELETE /api/v1/configuration/users/user-roles/user-role/rest-userrole-4
HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json
```

Creating a User Realm

To create a user realm:

```
REQUEST

POST /api/v1/configuration/users/user-realms/realm/ HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

{
    "accounting-server": "None",

    "authentication-group": "",

    "authentication-policy": {

        "browser": {

            "customized": "any-user-agent",

            "user-agent-patterns": {

                "user-agent-pattern": []

            }
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        },
        "certificate": {
            "cert-key-value-pairs": {
                "cert-key-value-pair": []
            },
            "customized": "allow-all-users"
        },
        "host-checker": {
            "enforce-all-policies": "false",
            "enforce-policy-list": null,
            "evaluate-all-policies": "false",
            "evaluate-logic": "all-policies-must-succeed",
            "evaluate-policy-list": null
        },
        "limits": {
            "guaranteed-minimum": null,
            "limit-concurrent-users": "false",
            "max-sessions-per-user": "1",
            "maximum": null
        },
        "password": {
            "primary-password-expiration-warning-days": "14",
            "primary-password-management": "true",
            "primary-password-minimum-length": "4",
            "primary-password-restricted": "allow-passwords-of-minimum-
length",
            "secondary-password-expiration-warning-days": "14",
            "secondary-password-management": "false",
            "secondary-password-minimum-length": "4",
            "secondary-password-restricted": "allow-passwords-of-minimum-
length"
        },
        "source-ip": {
            "customized": "any-ip",
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
            "ips": {
                "ip": []
            }
        }
    },
    "authentication-server": "AD server",
    "description": "",
    "device-server": "None",
    "directory-server": "AD server",
    "dynamic-policy": {
        "dynamic-policy-evaluation": "false",
        "refresh-interval": "60",
        "refresh-policies": "false",
        "refresh-roles": "false"
    },
    "editing-description": "false",
    "inbound-ifmap-attributes": "false",
    "migration-sharing-type": "enable-session-migration",
    "name": "rest-user-realm",
    "role-mapping-rules": {
        "rule": [
            {
                "name": "rest-admin-rule",
                "roles": [
                    "test1"
                ],
                "stop-rules-processing": "false",
                "user-name": {
                    "test": "is",
                    "user-names": [
                        "user1"
                    ]
                }
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
            }
        ],
        "user-selects-role": "false",
        "user-selects-roleset": "false"
    },
    "secondary-authentication-settings": {
        "authentication-must-succeed": "true",
        "name": "-",
        "password-input": "user",
        "predefined-password": "",
        "predefined-user-name": "",
        "user-name-input": "user"
    },
    "session-migration": "false"
}
```

RESPONSE

```
HTTP/1.1 201 CREATED
Content-Length: 122
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeed without warning or error!"
            }
        ]
    }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Deleting a User Realm

To delete a user realm:

```
REQUEST

DELETE /api/v1/configuration/users/user-realms/realm/rest-user-realm
HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json
```

Creating a Resource Profile

To create a web resource profile:

```
REQUEST

POST /api/v1/configuration/users/resource-profiles/web-profiles/web-
profile/ HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

{
    "custom": {
        "bookmarks": {
            "bookmark": [
                {
                    "apply": "all",
                    "description": "",
                    "name": "web-resourceprofile",
                    "new-window": "false",
                    "no-address-bar": "false",
                    "no-tool-bar": "false",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
                "roles": null,
                "url": "http://www.google.com"
            }
        ]
    },
    "client-authentication": [],
    "java-acl": [],
    "rewriting-options": {
        "ptp": [],
        "selective-rewriting": "false",
        "use-jsam": [],
        "use-wsam": []
    },
    "sso-basic-ntlm-kerberos": [],
    "sso-header": [],
    "sso-post": [],
    "url": "http://www.google.com",
    "web-compression": [],
    "webacl": [
        {
            "rules": {
                "rule": [
                    {
                        "action": "allow",
                        "name": "Allow http://www.google.com:80/*",
                        "resource": "http://www.google.com:80/*"
                    }
                ]
            }
        }
    ],
    "webcaching": []
},
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
    "description": "",
    "name": "web-resourceprofile",
    "roles": [
        "rest-userrole-3"
    ]
}
RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
    "result": {
        "warnings": [
            {
                "message": "The configuration has been implicitly changed"
            }
        ]
    }
}
```

Deleting a Resource Profile

To delete a web resource profile:

```
REQUEST
DELETE /api/v1/configuration/users/resource-profiles/web-profiles/web-
profile/web-resourceprofile HTTP/1.1
Host: 10.209.113.88
Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
Content-Type: application/json
RESPONSE
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

Creating a Resource Policy

To create a web resource policy:

```
REQUEST

POST /api/v1/configuration/users/resource-policies/web-policies/web-
acls/web-acl/ HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

{

    "action": "allow",

    "apply": "selected",

    "description": "",

    "name": "web-acl-policy",

    "parent-type": "none",

    "resources": [

        "1.1.1.1:80,443/*"

    ],

    "roles": [

        "rest-userrole-1"

    ],

    "rules": {

        "rule": []

    }

}

RESPONSE

HTTP/1.1 201 CREATED

Content-Length: 122

Content-Type: application/json

{

    "result": {

        "info": [

            {

                "message": "Operation succeed without warning or error!"
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            }
        ]
    }
}
```

Fetching a Resource Policy

To fetch a web resource policy:

```
REQUEST

GET /api/v1/configuration/users/resource-policies/web-policies/web-
acls/web-acl/name=web-acl-policy,parent-type=none HTTP/1.1

Host: 10.209.113.88

Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

Content-Length: 245

Content-Type: application/json

{
    "action": "allow",
    "apply": "selected",
    "description": "",
    "name": "web-acl-policy",
    "parent-type": "none",
    "resources": [
        "1.1.1.1:80,443/*"
    ],
    "roles": [
        "rest-userrole-1"
    ],
    "rules": {
        "rule": []
    }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Deleting a Resource Policy

To delete a web resource policy:

```
REQUEST

DELETE /api/v1/configuration/users/resource-policies/web-policies/web-acls/web-acl/name=web-acl-policy,parent-type=none HTTP/1.1

Host: 10.209.113.88

Authorization: Basic MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06

Content-Type: application/json

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json
```

Creating an AD Authentication Server

```
REQUEST

POST /api/v1/configuration/authentication/auth-servers/auth-server HTTP/1.1

Host: 10.209.114.152

Authorization: Basic QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06

Content-Type: application/json

{
    "ad": {
        "server-catalog": {
            "custom-variables": {
                "custom-variable": []
            },
            "expressions": {
                "custom-expression": []
            },
            "groups": {
                "ad-group": []
            }
        },
        "settings": {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            "additional-options": {
                "allow-trusted-domains": "false",
                "change-machine-password-after-every": "0",
                "enable-ntlm-protocol": "true",
                "enable-periodic-password-change-of-machine-account":
"false",
                "kerberos": "true",
                "max-domain-connections": "5",
                "ntlm-protocol": "ntlmv2"
            },
            "container-name": "Computers",
            "domain": "TEST",
            "kerberos-realm": "TEST.SAQACERTSERV.COM",
            "nodenames": [
                {
                    "computer-name": "0332MWK0NRP111",
                    "machine-hardware-id": "0332MOGWK0NRP111S",
                    "node": "localhost2"
                }
            ],
            "password-encrypted":
"3u+UR6n8AgABAAAAyCaUPKhCg3J/y46bhB4wz6mnupQH0oTHOTfTexJxP2k=",
            "save-credentials": "true",
            "username": "Administrator"
        }
    },
    "logical-name": "",
    "name": "AD-Server",
    "user-record-sync": "false"
}
```


RESPONSE


```
HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
"result": {
"warnings": [
{
"message": "The configuration has been implicitly changed"
}
            ]
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
            }
}
```

Deleting an AD Authentication Server

```
REQUEST

DELETE /api/v1/configuration/authentication/auth-servers/auth-
server/AD-Server HTTP/1.1

Host: 10.209.114.152

Authorization: Basic
QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06

Content-Type: application/json

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json
```

Creating an LDAP Authentication Server

```
REQUEST

POST /api/v1/configuration/authentication/auth-servers/auth-server HTTP/1.1

Host: 10.209.114.152

Authorization: Basic
QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06

Content-Type: application/json

{

    "ldap": {

        "server-catalog": {

            "attributes": {

                "user-attribute": [

                    {

                        "name": "cn"

                    },

                    {

                        "name": "department"

                    },
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
                    {
                        "name": "departmentNumber"
},
                    {
                        "name": "employeeNumber"
                    },
                    {
},
                    {
                        "name": "o"
                    },
                    {
                        "name": "ou"
                    },
                    {
                        "name": "sAMAccountName"
                    },
                    {
                        "name": "uid"
                    },
                    {
                        "name": "homeDirectory"
                    },
                    {
                        "name": "homeDrive"
                    },
                    {
"name": "wWWHomePage"
                    }
                ]
            },
            "custom-variables": {
                "custom-variable": []
            },
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            "expressions": {
                "custom-expression": []
            },
            "groups": {
                "user-group": []
            }
        },
        "settings": {
            "admin-dn":
"CN=Administrator,CN=Users,DC=test,DC=saqacertserv,DC=com",
            "admin-password-encrypted":
            }
"3u+UR6n8AgABAAAAQkYh+Te/ebXL7gSn+W6IEPOV2YFsaaikH2SVxkb8lTKzWhS1EPFlsNXBpuQP5sW
XfeOYfjmhQSRZ5DP/z9UhQ/l16DDne9/u7Lw67HyE/8Q=",
"attribute-to-update-at-server": "",
            "attribute-type": "type-integer",
            "attribute-value-to-update-at-server": "<LOGINTIMELDAP>",
            "authentication-required-to-search-ldap": "true",
            "backup-port-1": null,
            "backup-port-2": null,
            "backup-server-1": "",
            "backup-server-2": "",
            "connection-timeout": "15",
            "connection-type": "plain",
            "enable-attribute-update-at-server": "false",
            "group-base-dn": "",
            "group-filter": "",
            "ldap-server-type": "active-directory",
            "meetings": {
                "email-address": "mail",
                "full-name": "displayname",
                "name-attribute-mapping": "",
                "user-name": "samaccountname"
            },
            "member-attribute": "",
            "nested-group-level": "0",
            "port": "389",
            "query-attribute": "",
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
            "reverse-group-search": "false",
            "search-timeout": "60",
            "server": "10.209.124.88",
            "server-catalog": "catalog",
            "test-user-dn": "",
            "user-base-dn": "DC=test,DC=saqacertserv,DC=com",
            "user-filter": "samaccountname=<USER>",
            "validate-referral-cert": "verifyserverconfigured",
            "validate-server-cert": "false"
        }
    },
    "logical-name": "",
    "name": "LDAP-Server",
    "user-record-sync": "false"
}
RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
  "result": {
  "warnings": [
   {
     "message": "The configuration has been implicitly changed"
   }
  ]
          }
}
```

Creating a Radius Server

```
REQUEST
POST /api/v1/configuration/authentication/auth-servers/auth-server
HTTP/1.1
Host: 10.209.114.152
Authorization: Basic
QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06
Content-Type: application/json
{
    "logical-name": "",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
    "name": "Radius-Server",
    "radius": {
        "server-catalog": {
            "attributes": {
                "user-attribute": []
            },
            "custom-variables": {
                "custom-variable": []
            },
            "expressions": {
                "custom-expression": []
            }
        },
        "settings": {
            "accounting-port": "1813",
            "authenticate-with-tokens-onetimepassword": "false",
            "authentication-port": "1812",
            "backup-accounting-port": "1813",
            "backup-authentication-port": "1812",
            "backup-server": "10.209.126.179",
            "backup-shared-secret-encrypted":
"3u+UR6n8AgABAAAA2Th1sUV9vXDS9gRdMt1yCB4Ol6tacMTwhWsTlIFd7Q4=",
            "custom-radius-rules": {
                "custom-radius-rule": []
            },
            "interim-update-interval": null,
            "load-balance-auth": "false",
            "nasid": "",
            "nasipaddr": "10.209.113.88",
            "process-radius-disconnect": "false",
            "retries": "0",
            "server": "10.209.126.179",
            "shared-secret-encrypted":
"3u+UR6n8AgABAAAA2Th1sUV9vXDS9gRdMt1yCB4Ol6tacMTwhWsTlIFd7Q4=",
            "timeout": "30",
            "use-nc-assigned-ip": "false",
            "use-subsession-interim-update": "false",
            "user-name": "<USER>(<REALM>)[<ROLE SEP=\",\">]"
        }
    },
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
    "user-record-sync": "false"
}
```

RESPONSE

```
HTTP/1.1 201 CREATED
Content-Length: 128
Content-Type: application/json
{
  "result": {
  "warnings": [
   {
     "message": "The configuration has been implicitly changed"
   }
  ]
}
```

Modifying Radius Server Details

REQUEST

```
PUT /api/v1/configuration/authentication/auth-servers/auth-
server/Radius-Server HTTP/1.1
Host: 10.209.114.152
Authorization: Basic
QmJYZlZ6eER2Tzhodjh4NzhlU28vU1NNZ0tHelJJUHhsbC9pdjcrZlRxcz06
Content-Type: application/json
{
    "name": "Radius-Server",
    "radius": {
        "settings": {
            "backup-accounting-port": "1814",
            "backup-authentication-port": "1816",
            "backup-server": "2.2.2.2"
        }
    }

}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 128
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
}
```

Creating Sign-In-Policy

```
REQUEST

POST /api/v1/configuration/authentication/signin/urls/access-
urls/access-url/ HTTP/1.1

Host: 10.209.113.89

Authorization: Basic
MEthMXM0MmJraHpjYms0WFZCZ29Xb3k1Nk5NL3JqaDBwQ05iTmFhUlh5ST06

Content-Type: application/json

{

    "description": "",

    "enabled": "true",

    "page": "Default Sign-In Page",

    "realm-select": "pick-list",

    "url-pattern": "test/url3/",

    "user": {

        "enable-new-ux-pages": "false",

        "meeting-url": "*/meeting/",

        "post-authentication-signin-notification-id": "None",

        "post-authentication-signin-notification-skip": "false",

        "pre-authentication-signin-notification-id": "None",

        "realms": [

            "Users"

        ]

    }

}
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
RESPONSE

HTTP/1.1 201 CREATED

Content-Length: 128

Content-Type: application/json

{

    "result": {

        "info": [

            {

                "message": "Operation succeeded without warning or
error!"

            }

        ]

    }

}
```

Deleting Sign-in-Policy

```
REQUEST

DELETE /api/v1/configuration/authentication/signin/urls/access-
urls/access-url/test%5C%2Furl3%5C%2F HTTP/1.1

Host: 10.209.113.89

Authorization: Basic
MEthMXM0MmJraHpjYms0WFZCZ29Xb3k1Nk5NL3JqaDBwQ05iTmFhUlh5ST06

Cache-Control: no-cache

RESPONSE

HTTP/1.1 204 NO CONTENT

Content-Length: 0

Content-Type: application/json
```

Disabling Sign-in-URL

```
REQUEST

PUT /api/v1/configuration/authentication/signin/urls/access-urls/access-
url/test%5C%2Furl1%5C%2F/enabled HTTP/1.1

Host: 10.209.113.89

Authorization: Basic
MEthMXM0MmJraHpjYms0WFZCZ29Xb3k1Nk5NL3JqaDBwQ05iTmFhUlh5ST06
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Content-Type: application/json
{
    "enabled": "false"
}
RESPONSE
HTTP/1.1 200 OK
Content-Length: 128
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
}
```

Creating a Web Bookmark for a Role

To create a web bookmark for a role:

```
REQUEST
POST /api/v1/configuration/users/user-roles/user-role/rest-userrole-
1/web/web-bookmarks/bookmark HTTP/1.1
Host: 10.209.113.88
Authorization: Basic
MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
Content-Type: application/json
Cache-Control: no-cache
{
    "auto-allow": "disable",
    "description": "",
    "name": "webbm",
    "new-window": "false",
    "no-address-bar": "false",
    "no-tool-bar": "false",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
    "parent": "--none--",
    "standard": {
        "url": "http://www.yahoo.com"
     }
}
RESPONSE
HTTP/1.1 201 CREATED
Content-Length: 122
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeed without warning or error!"
            }
        ]
    }
}
```

Reordering

For re-ordering existing ordered elements in the configuration, a PUT API can be used with an 'order' suffix. This API can be used to reorder any ordered element in the configuration including role-mapping-rules, resource policies and ACLs.

Example: Reorder existing role-mapping-rules in a specific realm.

```
REQUEST
PUT /api/v1/configuration/users/user-realms/realm/testRealm/role-
mapping-rules/rule/order HTTP/1.1
Host: 10.209.112.106
Authorization: Basic
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06
Content-Type: application/json
{
  "rule": [
    {
      "href": "/api/v1/configuration/users/user-
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
realms/realm/testRealm/role-mapping-rules/rule/rule3"

    },

    {

      "href": "/api/v1/configuration/users/user-
realms/realm/testRealm/role-mapping-rules/rule/rule1"

    }

  ]

}
```

RESPONSE

```
HTTP/1.1 200 OK

content-length: 122

content-type: application/json

{

    "result": {

        "info": [

            {

                "message": "Operation succeed without warning or error!"

            }

        ]

    }

}
```

Fetching the Resource with Multiple Identifiers

Example: Retrieve one of SNMP Trap server configured on PCS device

REQUEST

```
GET /api/v1/configuration/system/log/snmp/localhost2/trap-servers/trap-
server/ip=1.1.1.1,port=162 HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
T0o1dzVpK3g4U0dKV0d1TkJCdWlwVzREaUc0SjZvbkExMVljc0RtNU14bz06
```

RESPONSE

```
HTTP/1.1 200 OK

content-length: 65

content-type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
{
    "community": "public",
    "ip": "1.1.1.1",
    "port": "162"
}
```

Updating Resource Identified Using Multiple Identifiers

Example: Updating the community string for specific SNMP trap server identified by IP and port

```
REQUEST

PUT /api/v1/configuration/system/log/snmp/localhost2/trap-servers/trap-
server/ip=1.1.1.1,port=162/community HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
T0o1dzVpK3g4U0dKV0d1TkJCdWlwVzREaUc0SjZvbkExMVljc0RtNU14bz06

Content-Type: application/json

{
    "community": "pulsesecure"
}

RESPONSE

HTTP/1.1 200 OK

content-length: 122

content-type: application/json

{
    "result": {
        "info": [
            {
                "message": "Operation succeed without warning or error!"
            }
        ]
    }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Fetching Active Number of HTML5 Sessions

```
REQUEST

GET /api/v1/stats/active-html5-sessions HTTP/1.1

Host: 10.96.116.40

Authorization: Basic
b1hBV3FaTktKQzhaOU5MNTNsLzJGQXZmNWZ1TGhFSUUyUlVJVDlaRnFVYz06

Content-Type: application/json

RESPONSE

HTTP/1.1 200 OK

content-length: 32

content-type: application/json

{

    "active-html5-sessions": 3

}
```

Updating Password in Clear Text

Example: Updating password of System Local User.

```
REQUEST


PUT /api/v1/configuration/authentication/auth-servers/auth-
server/System%20Local/local/users/user/user0001/password-cleartext
HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
T0o1dzVpK3g4U0dKV0d1TkJCdWlwVzREaUc0SjZvbkExMVljc0RtNU14bz06

Content-Type: application/json

{

   "password-cleartext": "Psecure"

}


RESPONSE

HTTP/1.1 200 OK
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
content-length: 128

content-type: application/json

{

   "result": {

     "warnings": [

       {

          "message": "The configuration has been implicitly changed"

       }

     ]

   }

}
```

Applying Authcode and Downloading Licenses from PCLS on VA-SPE|PSA-V

In PCS 8.3R4|PPS 5.4R4, this REST API can be used to download the license key from PCLS and install on the Virtual Appliance.

```
REQUEST
PUT /api/v1/license/auth-code HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Length: 35
Content-Type: application/json
{
  "auth-code":"<auth-code-to-apply>"
}
RESPONSE
HTTP/1.1 200 OK
Content-Type: application/json
Content-Length: 191
{
   "result": {
     "info": [
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
       {"message": "Installed new license key \"landmark utility
prestige trip mayor diesel faucet summer prestige income heritage\""}
     ]
   }
}
```

Applying License

REQUEST

```
PUT /api/v1/license/license-key?action=install HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Type: application/json
{
   "keys":[
     "key1",
     “key2”,
     ….
   ]
}
Example:
{
   "keys":[
     "operation tree crayon holiday kingdom lasso doorway square
dish modem gecko",
     "buffalo safety inch topaz banquet nitrogen garnish step
recital wedge trace"
   ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
    "result": {
       "info": [
        {
          "message": "Installed licenses"
        }
       ]
    }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Deleting License

REQUEST

```
PUT /api/v1/license/license-key?action=delete HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Type: application/json
{
   "keys":[
      "key1",
      “key2”,
      ….
   ]
}

Example:
{
   "keys":[
      "operation tree crayon holiday kingdom lasso doorway square
dish modem gecko",
      "buffalo safety inch topaz banquet nitrogen garnish step
recital wedge trace"
   ]
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
   "result": {
     "info": [
       {
          "message": "Deleted <number> licenses"
       }
     ]
   }
}
```

© 2020 by Pulse Secure, LLC. All rights reserved

Getting License Clients

REQUEST

```
GET /api/v1/license/license-clients HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "license_clients": [
    {
      "feature_capacities": [
        {
          "feature_name": "add_user_count",
          "leased_value": 25
        },
        {
          "feature_name": "onboard",
          "leased_value": 0
        },
        {
          "feature_name": "embeddedrdpapplet",
          "leased_value": 0
        },
        {
          "feature_name": "vm_cores_leasable",
          "leased_value": 4
        },
        {
          "feature_name": "add_meeting_user_count",
          "leased_value": 0
        },
        {
          "feature_name": "cloudsecure_count",
          "leased_value": 0
        },
        {
          "feature_name": "named_user_count",
          "leased_value": 0
        },
        {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        "feature_name": "ueba",
        "leased_value": 0
      }
    ],
    "last_renewal": "Wed, 04 Dec 2019 06:32:26 GMT",
    "machine_id": "VASPH3944M9D8551S",
    "name": "va_spe_3_3_125_4"
  },
  {
    "feature_capacities": [
      {
        "feature_name": "add_user_count",
        "leased_value": 25
      },
      {
        "feature_name": "onboard",
        "leased_value": 0
      },
      {
        "feature_name": "embeddedrdpapplet",
        "leased_value": 0
      },
      {
        "feature_name": "vm_cores_leasable",
        "leased_value": 4
      },
      {
        "feature_name": "add_meeting_user_count",
        "leased_value": 0
      },
      {
        "feature_name": "cloudsecure_count",
        "leased_value": 0
      },
      {
        "feature_name": "named_user_count",
        "leased_value": 0
      },
      {
        "feature_name": "ueba",
        "leased_value": 0
      }
    ],
    "last_renewal": "Thu, 05 Dec 2019 13:45:31 GMT",
    "machine_id": "VASPHXVK2E117PM8S",
    "name": "va_spe_3_3_125_8"
  },
]
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
}
```

Getting License Report from License Server

REQUEST

```
GET /api/v1/license/report HTTP/1.1
Host: 10.209.125.7
Authorization: Basic
TnBDUk1veFFFQTJKZjM0S2ZxV2JKUlhRaDJaWGFrYnkvWVpTR3hhNTdmbz0=
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
```

License Usage Report

```
{
   "LicenseUsageReport": {
     "MachineID": "VASPMMXXXXXXXX",
     "build-number": "4762",
     "cumulative-report": {…},
     "granular-report": {…},
     "cluster-granular-report": {…},
     "time-stamp": "Mon Jan 13 20:04:40 2020",
     "version": "9.1"
   }
}
```

Cumulative Report
https://<license-server>/api/v1/license/report/cumulative-report

```
{
   "cumulative-report": {
     "add-meeting-user-count": {
       "Year":[
        {
          "Month": [
            {
              "Date": [
                {
                  "Leased": "0",
                  "Maximum": "30",
                  "id": "06"
                }
                {…},
                {…},
                {…},
                {…}
              ]
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
                "Leased": "0",
                "Maximum": "30",
                "id": "Jan",
              }
              {…}
            ]
            "id": "2020"
          }
          {…}
        ]
    }
}
```


Granular Report

https://<license-server>/api/v1/license/report/granular-report


```
{
  "license-client": [
   {
     "add-user-count": {
       "Year": [
         {
           "Month": [
             {
               "Date": [
                {…},
                {…},
                {…},
                {…}
               ]
               "Leased": "0",
               "Maximum": "0",
               "id": "Jan"
             }
           ],
           "id": "2020"
         }
       ]
      },
      "name": "PSA_V_10_209_125_101",
      "software-version": "7.4"
   },
   {…}
}
```


Cluster Granular Report

https://<license-server>/api/v1/license/report/cluster-granular-report


```
{
   "add-user-count": {
     "Year": [
```


© 2020 by Pulse Secure, LLC. All rights reserved

```
       {
         "Month": [
           {
             "Date": [
               {
                 "Leased": "40",
                 "Maximum": "21",
                 "client-node": "node63lc,node66lc",
                 "id": "24"
               },
               {
                 "Leased": "40",
                 "Maximum": "1",
                 "client-node": "node63lc,node66lc",
                 "id": "25"
               },
               {
                 "Leased": "40",
                 "Maximum": "1",
                 "client-node": "node63lc,node66lc",
                 "id": "26"
               }
             ],
             "Leased": "40",
             "Maximum": "21",
             "id": "Feb"
           }
         ],
         "id": "2020"
       }
     ]
    },
    "cluster-name": "liccluster"
}
```


The following extensions of the API are supported:

1. /api/v1/license/report – entire license report in JSON
2. /api/v1/license/report/cumulative-report – The cumulative report.
   - Following trace-down options available here
     i. /api/v1/license/report/cumulative-report/<license-feature-type>
     ii. /api/v1/license/report/cumulative-report/<license-feature-type>/<year>
     iii. /api/v1/license/report/cumulative-report/<license-feature-type>/<year>/<month>
     iv. /api/v1/license/report/cumulative-report/<license-feature-type>/<year>/<month>/<day>

3. /api/v1/license/report/granular-report – License usage report per license client.
   - Following trace-down options available here
     i. /api/v1/license/report/granular-report/<license-client>
     ii. /api/v1/license/report/granular-report/<license-client>/<add-user-count>

© 2020 by Pulse Secure, LLC. All rights reserved

iii. /api/v1/license/report/granular-report/<license-client>/<add-user-count>/<year>

iv. /api/v1/license/report/granular-report/<license-client>/<add-user-count>/<year>/<month>

v. /api/v1/license/report/granular-report/<license-client>/<add-user-count>/<year>/<month>/<day>

Example:

API - /api/v1/license/report/granular-report/node63lc/add-user-count/2020/Mar/20


```
{
    "Leased": 40,
    "Maximum": 14,
    "id": "20"
}
```


4. /api/v1/license/report/cluster-granular-report – License usage report per license client cluster.

- Following trace-down options available here

i. /api/v1/license/report/cluster-granular-report/<license-client>

ii. /api/v1/license/report/cluster-granular-report/<license-client>/<add-user-count>

iii. /api/v1/license/report/cluster-granular-report/<license-client>/<add-user-count>/<year>

iv. /api/v1/license/report/cluster-granular-report/<license-client>/<add-user-count>/<year>/<month>

v. /api/v1/license/report/cluster-granular-report/<license-client>/<add-user-count>/<year>/<month>/<day>

Example:

API - /api/v1/license/report/cluster-granular-report/liccluster/add-user-count/2020/Mar/22


```
{
    "Leased": 40,
    "Maximum": 16,
    "cluster-member": [
        "node63lc",
        "node66lc"
    ],
    "id": "22"
}
```


© 2020 by Pulse Secure, LLC. All rights reserved

Enabling/Disabling ICE License

Enabling ICE License

```
Content of ice_enable.json file:
more ice_enable.json
{
   "mode": "enabled"
}
```

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/license/ice -X PUT -H
"Content-Type: application/json" -d @ice_enable.json

Example:
curl -k -u TVGJ9xV9XvuA1JDB1nPkjC5BilAQAhUMn2dPHLZgP/o=:
https://10.209.125.4/api/v1/license/ice -X PUT -H "Content-Type:
application/json" -d @ice_enable.json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "ICE license is enabled"
      }
    ]
  }
}
```

Disabling ICE License

```
Content of ice_disable.json file:
more ice_disable.json
{
   "mode" : "disabled"
}
```

REQUEST

```
curl -k -u TVGJ9xV9XvuA1JDB1nPkjC5BilAQAhUMn2dPHLZgP/o=:
https://10.209.125.4/api/v1/license/ice -X PUT -H "Content-Type:
application/json" -d @ice_disable.json
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "ICE license is disabled"
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
      }
    ]
  }
}
```

Getting the Current Status of ICE License

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/license/ice

Example:
curl -k -u TVGJ9xV9XvuA1JDB1nPkjC5BilAQAhUMn2dPHLZgP/o=:
https://10.209.125.4/api/v1/license/ice
```

RESPONSE

ICE License Enabled

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "mode": "enabled"
}
```

ICE License Disabled

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "mode": "disabled"
}
```

Exporting TOTP Users from One Device to Another Device

REQUEST

```
curl -k -u <api-key>: https://pcs-ip>/api/v1/totp/<TOTP-AUTH-SERVER-NAME>/users
```

NOTE: This API can be executed only on TOTP server configured as Local (and not Remote).

Example:

```
curl -k -u X1O3oczUMJbhI8ba3Ov0McD54QCwBgwpSHwOGUVu5Ck=:
https://10.209.115.20/api/v1/totp/Google%20TOTP%20Auth%20Server/users
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Length: 191
Content-Type: application/json
{
      "users":
      "21ubWxSvAwABAAAAlx9igwcQok9s+MV0zg/b+oer3z7Kj0iXbVzJ+qDMiguTtWZaxnGHGTGQE
      cHD7BTMGjz1QYbO00zBF+6DGp2y/9pj+8Wf4SXTQbYIeDomT4w2Kl4oc1EZhFruWLWnll+58x2
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
      b0kxsURCb+P0It8K+msqFXBhOEDY7l0W4+P+A8UZaz6In/gMq8Qd766i7RN1oZ+hzHUMYJUB72
      tzIQ+CiA8tTv6aweC6TGy9/a9C6vVbLY0+ZUgGTffWzJxcoZbEbdwiCFoZyex5UWTUFIj0Z4XA
      PoZ4HTWZsxP5YwXcJpsnbOzCqW/dTB6WpYWYp6R+MUn2yu/hZeu7z1qVhXlr8bK5LifH/u6J76
      SpErL1eELh1bYF17DWPfo6xspG7rffhs2k9vPVB1oq2kud+42hPo6vZaMfcwaz9lKRrftIgAu2
      o3JBJfdNHrUTOu2+Y6Qmc0in6MfIBNNrVr9D6hdWmIdrNr7PXHa4uJoP+CAuOp3OamTox2sgmv
      E7YNjC0SlSPgyFfx0kfzCb2K3Mrcq1UuJUJLhK7L3lne4f1QiWKoZ8q8zluaV+eRSJHBez9Pjo
      +LzBpYwoXStduOC20FVY4+KCHDasufdAOCD/Lga4mFFE5ItAui18ObOfRtxLvoZUIuGS8w019m
      bRaNDlVa52sUzuZBClqx+4lueBCQYEUNrDrHVG0AzqUBbAeL+WV8VRJrxVW8sIlArqY8n29pD6
      6BozsGKoxBqXSe/fZxEDu9ZqI4xfzSCCsfqTiv0LAM4p+cZekhcjvRwtuImNjX+qj7A=="
}
```

Importing TOTP Users from One Device to Another Device

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/totp/<TOTP-AUTH-SERVER-NAME>/users -H
"Content-Type: application/json" -d @totp_users.json -X POST
```

NOTE: This API can be executed only on TOTP server configured as Local (and not Remote).

Example:

```
curl -k -u K7Z7xA54AKnv1++kcViamCCiUrEBgMSP+sHKar4EcKY=:
https://10.209.125.4/api/v1/totp/TOTP_SERVER/users -H "Content-Type:
application/json" -d @totp_users.json -X POST
{
      "users":
      "21ubWxSvAwABAAAAlx9igwcQok9s+MV0zg/b+oer3z7Kj0iXbVzJ+qDMiguTtWZaxnGHGTGQE
      cHD7BTMGjz1QYbO00zBF+6DGp2y/9pj+8Wf4SXTQbYIeDomT4w2Kl4oc1EZhFruWLWnll+58x2
      b0kxsURCb+P0It8K+msqFXBhOEDY7l0W4+P+A8UZaz6In/gMq8Qd766i7RN1oZ+hzHUMYJUB72
      tzIQ+CiA8tTv6aweC6TGy9/a9C6vVbLY0+ZUgGTffWzJxcoZbEbdwiCFoZyex5UWTUFIj0Z4XA
      PoZ4HTWZsxP5YwXcJpsnbOzCqW/dTB6WpYWYp6R+MUn2yu/hZeu7z1qVhXlr8bK5LifH/u6J76
      SpErL1eELh1bYF17DWPfo6xspG7rffhs2k9vPVB1oq2kud+42hPo6vZaMfcwaz9lKRrftIgAu2
      o3JBJfdNHrUTOu2+Y6Qmc0in6MfIBNNrVr9D6hdWmIdrNr7PXHa4uJoP+CAuOp3OamTox2sgmv
      E7YNjC0SlSPgyFfx0kfzCb2K3Mrcq1UuJUJLhK7L3lne4f1QiWKoZ8q8zluaV+eRSJHBez9Pjo
      +LzBpYwoXStduOC20FVY4+KCHDasufdAOCD/Lga4mFFE5ItAui18ObOfRtxLvoZUIuGS8w019m
      bRaNDlVa52sUzuZBClqx+4lueBCQYEUNrDrHVG0AzqUBbAeL+WV8VRJrxVW8sIlArqY8n29pD6
      6BozsGKoxBqXSe/fZxEDu9ZqI4xfzSCCsfqTiv0LAM4p+cZekhcjvRwtuImNjX+qj7A=="
}
```

RESPONSE

```
HTTP/1.1 200 OK
content-length →47
Content-Type: application/json
{
      “message' => 'Successfully imported user data'
}
```

Resetting TOTP User

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/totp/<TOTP-AUTH-SERVER-
NAME>/users/<totp-user>?operation=reset -X PUT
```

© 2020 by Pulse Secure, LLC. All rights reserved

Example :

```
curl -k -u nNuALLLWajGujVF2yT4qyP4nYxy/nwXxBKp0CHu2AZQ=:
https://3.3.125.4/api/v1/totp/TOTP_SERVER/users/qauser1001?operation=reset
-X PUT
```

RESPONSE

Scenario: TOTP user reset

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "result": {
    "info": [
      {
        "message": "TOTP user 'qauser1001' under Authserver
'TOTP_SERVER' has been reset"
      }
    ]
  }
}
```

Scenario: TOTP user does not exist

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "result": {
    "errors": [
      {
        "message": "TOTP user 'qauser1001' is not present under
Authserver 'TOTP_SERVER'"
      }
    ]
  }
}
```

Unlocking TOTP User

REQUEST

```
curl -k -u <api-key>: https://<pcs-ip>/api/v1/totp/<TOTP-AUTH-SERVER-
NAME>/users/<totp-user>?operation=unlock -X PUT
```

Example :

```
curl -k -u nNuALLLWajGujVF2yT4qyP4nYxy/nwXxBKp0CHu2AZQ=:
https://3.3.125.4/api/v1/totp/TOTP_SERVER/users/qauser1001?operation=unlock
-X PUT
```

RESPONSE

Scenario: TOTP user unlocked

```
HTTP/1.1 200 OK
Content-Type: application/json
{
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
  "result": {
    "info": [
     {
       "message": "TOTP user 'qauser1001' under Authserver
'TOTP_SERVER' has been unlocked"
     }
   ]
  }
}
```

Scenario: TOTP user cannot be unlocked

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "result": {
    "errors": [
      {
        "message": "Error: Only locked users can be unlocked"
      }
    ]
  }
}
```

Sample Error Responses

400 BAD REQUEST

```
REQUEST

PUT /api/v1/configuration/users/user-realms/realm/testRealm/role-
mapping-rules/rule/rule1 HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06

Content-Type: application/json

{

    "name": "rule1",

    "roles": [

        "Users"

    ],

    "stop-rules-processing": "false",

    "user-name": {

        "test": "is",
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        "user-names": [
            "*",
        ]
    }
}
```

RESPONSE

```
HTTP/1.1 400 BAD REQUEST
content-length: 92
content-type: application/json
{
"message": "The browser (or proxy) sent a request that this server could not understand."
}
```

Solution: Invalid JSON body content in Request. Please check if JSON is valid.

REQUEST

```
PUT /api/v1/configuration/users/user-roles/user-role/rest-userrole-1 HTTP/1.1
Host: 10.209.113.88
Authorization: Basic MVhDbDJTSUhkV3ZjUkd6WXM1T1V3MU5wbHNmemJPbTJxSHI2NVZCdXp5bz06
{
    "name": "rest-userrole-1",
    "web": {
        "web-bookmarks": {
            "bookmark": [
                {
                    "auto-allow": "disable",
                    "description": "",
                    "name": "web-bm-1",
                    "new-window": "false",
                    "no-address-bar": "false",
                    "no-tool-bar": "false",
                    "parent": "--none--",
                    "standard": {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
                        "url": "http://www.yahoo.com"
                    }
                }
            ]
        },
        "web-options": {
            "browsing-untrusted-sslsites": "true",
            "flash-content": "false",
            "hpxproxy-connection-timeout": "1800",
            "http-connection-timeout": "240",
            "java-applets": "true",
            "mask-hostname": "false",
            "persistent-cookies": "false",
            "rewrite-file-urls": "false",
            "rewrite-links-pdf": "false",
            "unrewritten-page-newwindow": "false",
            "user-add-bookmarks": "false",
            "user-enter-url": "false",
            "users-bypass-warnings": "false",
            "warn-certificate-issues": "true",
            "websocket-connection-timeout": "900"
        }
    }
}
```

RESPONSE

```
HTTP/1.1 400 BAD REQUEST
Content-Length: 99
Content-Type: application/json
{
    "result": {
        "errors": [
            {
                "message": "Accepts only JSON."
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
            }
        ]
    }
}
```

Note: Include the “Content-Type” header in the request with a value “application/json” as used in the examples above.

403 Forbidden

```
REQUEST
GET /api/v1/auth HTTP/1.1
Host: 10.209.112.106
Authorization: Basic YWRtaW5kYjpkYW5hMTIz
Content-Type: application/json
RESPONSE
HTTP/1.1 403 Forbidden
cache-control: no-store
connection: Keep-Alive
content-type: text/html; charset=utf-8
expires:-1
keep-alive: timeout=15
strict-transport-security →max-age=31536000
transfer-encoding: chunked
```

Solutions:

1. Make sure admin user used for authentication has "Allow access to REST APIs" option enabled from admin UI
2. Admin Username and Password passed in Authorization header are correct
3. If api_key is available, use api_key value as username and password as empty in authorization header

404 NOT FOUND

```
REQUEST
GET /api/v1/configuration/users/user-realms/realm/testRealm/role-
mapping-rules/rule HTTP/1.1
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Host: 10.209.112.106

Authorization: Basic
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06

RESPONSE

HTTP/1.1 404 NOT FOUND

content-length: 213

content-type: application/json

{

    "result": {

        "errors": [

            {

                "message": "Invalid resource path; use \"users/user-
realms/realm/testRealm/role-mapping-rules/rule/<resource-id>\" to access
a specific resource"

            }

        ]

    }

}
```

Solution: Resource-id should be passed in Resource path as shown in example below.

```
REQUEST

GET /api/v1/configuration/users/user-realms/realm/testRealm/role-
mapping-rules/rule/rule1 HTTP/1.1

Host: 10.209.112.106

Authorization: Basic
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06

RESPONSE

HTTP/1.1 200 OK

content-length: 167

content-type: application/json

{

    "name": "rule1",

    "roles": [

        "Users"

    ],
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
    "stop-rules-processing": "false",
    "user-name": {
        "test": "is",
        "user-names": [
            "*"
        ]
    }
}
```

Solution: Invalid JSON body content in Request. Please check if JSON is valid.

422 UNPROCESSABLE ENTITY

```
REQUEST
POST /api/v1/configuration/users/user-realms/realm/testRealm/role-
mapping-rules/rule/ HTTP/1.1
Host: 10.209.112.106
Authorization: Basic
Y1VPZE1XZ1ZubVEvVnIrcWwrd3lJY3F0Y05WTGhDVkx1M0wrdk5YR3hzVT06
Content-Type: application/json
{
    "name": "rule2",
    "roles": [
        "Users",
        "testRole1"
    ],
    "stop-rules-processing": "false",
    "user-name": {
        "test": "is",
        "user-names": [
            "user1"
        ]
    }
}
RESPONSE
HTTP/1.1 422 UNPROCESSABLE ENTITY
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
content-length: 368

content-type: application/json

{

    "result": {

        "errors": [

            {

                "message": "[/users/user-
realms/realm[name=testRealm]/role-mapping-rules/rule[name=rule2]/roles]
Invalid reference: no 'User Roles' object found with identifier
'testRole1'."

            },

            {

                "message": "Failed to resolve path references"

            },

            {

                "message": "Commit failed"

            }

        ]

    }

}
```

Solution: Make sure to have all the referenced resources are created first using POST call and then repeat.

Limitations

1. Configuration of large data objects is not qualified- ESAP, Pulse Client package, Custom Sign-in page, applets, and so on.
2. Resource names similar to resource tags e.g. vlans, roles, etc. should be avoided while creating new resources.

© 2020 by Pulse Secure, LLC. All rights reserved

PPS-Specific Configurations Using REST APIs

- Creating the HC Policy
- Deleting the HC Policy
- Creating the Infranet Enforcer
- Deleting the Infranet Enforcer
- Creating a Resource Policy
- Deleting a Resource Policy
- Creating a RADIUS Client
- Deleting a RADIUS Client
- Creating a RADIUS Attribute Policy
- Deleting a RADIUS Attribute Policy
- Creating SNMP Device
- Deleting SNMP Device
- Creating SNMP Policy
- Deleting SNMP Policy
- Creating Device Group - TACACS+
- Deleting Device Group- TACACS+
- Creating TACACS+ Client
- Deleting TACACS+ Client
- Creating Shell Policies
- Deleting Shell Policies
- Creating Admission Control Client
- Deleting Admission Control Client
- Creating Admission Control Policy
- Deleting Admission Control Policy
- Getting Authentication API Key
- Pulse Policy Secure Alert Based Admission Control APIs
- Profiler REST APIs

© 2020 by Pulse Secure, LLC. All rights reserved

Creating the HC Policy

REQUEST

```
POST api/v1/configuration/authentication/endpoint/host-
checker/policies/policy HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "policy-name": "HC",
    "regular": {
        "platforms": {
            "chromeos": {
                "dashboard": {
                    "consider-for-reporting": "true"
                },
                "remediation": {
                    "custom-instructions": "",
                    "enable-custom-instructions": "false",
                    "send-reason-strings": "true"
                }
            },
            "windows": {
                "dashboard": {
                    "consider-for-reporting": "true"
                },
                "remediation": {
                    "custom-instructions": "",
                    "delete-files": "false",
                    "enable-custom-instructions": "false",
                    "files": null,
                    "kill-processes": "false",
                    "processes": null,
                    "send-reason-strings": "true"
                },
                "rule-expression": {
                    "custom-expression": "",
                    "requirement": "all"
                },
                "rules": {
                    "advancedRule": [],
                    "firewall-rules": {
                        "firewall-rule": [
                            {
                                "needs-monitoring": "false",
                                "product-list": null,
                                "product-selection-option":
"specific",
                                "rule-name": "rule1",
                                "select-specific-product": "false",
                                "select-specific-vendor": "true",
                                "selected-product-list": {
                                   "product-info": [
                                        {
                                            "product-name":
"Windows Firewall (10.x)",
                                            "turn-on-firewall":
"true"
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
                                        },
                                        {
                                            "product-name":
"Windows Firewall (6.x)",
                                            "turn-on-firewall":
"false"
                                        }
                                    ]
                                },
                                "turn-on-firewall-all": "false",
                                "vendor-list": [
                                    "Microsoft Corporation"
                                ]
                            }
                        ]
                    }
                }
            }
        }
    }
}
```

RESPONSE

```
{
    "result": {
        "warnings": [
            {
                "message": "The configuration has been implicitly
changed"
            }
        ]
    }
}
```

Deleting the HC Policy

REQUEST

```
DELETE api/v1/configuration/authentication/endpoint/host-
checker/policies/policy/HC  HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

Creating the Infranet Enforcer

REQUEST

```
POST api/v1/configuration/uac/infranet-
enforcer/connections/infranet-enforcer HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "idp-for-local-sessions-only": "true",
    "junos": {
        "location-group": "- No 802.1X -",
        "password-encrypted":
"3u+UR6n8AgABAAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
    },
    "name": "SRX",
    "serial-number": [
        "ABCNWPWFS"
    ],
    "severity-filter": "medium",
    "use-idp": "false"
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
}
```

Deleting the Infranet Enforcer

REQUEST

```
DELETE api/v1/configuration/uac/infranet-
enforcer/connections/infranet-enforcer/SRX HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

Creating a Resource Policy

REQUEST

```
POST api/v1/configuration/uac/infranet-enforcer/resource-access-
policies/resource-access-policy/ HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "action": "allow-access",
    "apply": "all-roles",
    "apply-ie-options": "all-options",
    "deny-message": "",
    "description": "",
    "ie-options": [],
    "infranet-enforcer": [
        "(all)"
    ],
    "name": "Resource Policy",
    "resources": [
        "10.25.15.0/24:*"
    ],
    "roles": null,
    "vsys": ""
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
}
```

Deleting a Resource Policy

REQUEST

```
DELETE api/v1/configuration/uac/infranet-enforcer/resource-access-
policies/resource-access-policy/Resource%20Policy HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

Creating a RADIUS Client

REQUEST

```
POST /api/v1/configuration/uac/network-access/radius-clients/radius-
client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "coa-support": "false",
    "description": "",
    "disconnect-support": "true",
    "dynamic-auth-port": "3799",
    "enable": "true",
   "gatewayid": "",
    "ip-address": "10.204.88.12",
    "ip-address-range": "1",
    "kek-encrypted": "",
    "key-wrap-format": "HEX",
    "key-wrap-support": "false",
    "location-group": "Default",
    "mack-encrypted": "",
    "make-model": "Ruckus Wireless",
    "name": "Ruckus",
    "ruckus-certificate-verification": "false",
    "ruckus-password-encrypted": "",
    "shared-secret-encrypted":
"3u+UR6n8AgABAAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
}
```

Deleting a RADIUS Client

REQUEST

```
Delete /api/v1/configuration/uac/network-access/radius-clients/radius-
client/Ruckus HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

Creating a RADIUS Attribute Policy

REQUEST

```
POST /api/v1/configuration/uac/network-access/radius-attribute/radius-
attributes-policies/radius-attribute-policy HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "apply": "all",
    "description": "",
    "location-group": [
        "Guest"
    ],
    "name": "Return Attribute policy",
    "network-interface": "automatic",
    "open-port": "false",
    "return-attribute-flag": "false",
    "return-attributes": {
        "return-attribute": []
    },
    "roles": null,
    "send-session-timeout-by-default": "false",
    "send-termination-action-by-default": "false",
    "vlan": "65",
    "vlan-check": "true"
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
}
```

Deleting a RADIUS Attribute Policy

REQUEST

```
DELETE  /api/v1/configuration/uac/network-access/radius-
attribute/radius-attributes-policies/radius-attribute-
policy/Return%20Attribute%20policy/HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Content-Length: 0
Content-Type: application/json
```

Creating SNMP Device

REQUEST

```
POST /api/v1/configuration/uac/snmpEnforcement/clients/client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "default-vlan": "0",
    "description": "",
    "enable": "true",
    "ip-address": "10.204.88.12",
    "location-group": "none",
    "model": "Ruckus Wireless",
    "name": "ruckus",
    "read-auth-password-encrypted": "",
    "read-auth-protocol": "md5",
    "read-priv-password-encrypted": "",
    "read-priv-protocol": "",
    "read-security-level": "auth",
    "read-username": "public",
    "snmp-enforcement": "false",
    "snmp-version": "V2",
    "ssh-passphrase-encrypted": "",
    "ssh-port-number": "22",
    "ssh-private-key-encrypted": "",
    "ssh-user-name": "",
    "ssh-user-password-encrypted": "",
    "sys-contact": "https://support.ruckuswireless.com/contact_us",
    "sys-description": "Ruckus Wireless ZD1200",
    "sys-location": "350 West Java Dr. Sunnyvale, CA 94089 US",
    "sys-name": "ruckus",
    "trap-auth-password-encrypted": "",
    "trap-auth-protocol": "md5",
    "trap-priv-password-encrypted": "",
    "trap-priv-protocol": "",
    "trap-security-level": "auth",
    "trap-username": "public",
    "use-samecredential": "true",
    "write-auth-password-encrypted": "",
    "write-auth-protocol": "md5",
    "write-priv-password-encrypted": "",
    "write-priv-protocol": "",
    "write-security-level": "auth",
    "write-username": "public"
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
error!"
            }
        ]
    }
}
```

Deleting SNMP Device

REQUEST

```
DELETE
/api/v1/configuration/uac/snmpEnforcement/clients/client/ruckus/HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating SNMP Policy

REQUEST

```
POST  /api/v1/configuration/uac/snmpEnforcement/snmpPolicies/policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "apply-to-roles": "selected",
    "description": "",
    "location-group": "Guest Wired",
    "name": "SNMP policy",
    "roles": [
        "Guest Wired Restricted"
    ],
    "vlan": "65"
}
```

RESPONSE

```
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or
error!"
            }
        ]
    }
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
}
```

Deleting SNMP Policy

```
REQUEST
DELETE
/api/v1/configuration/uac/snmpEnforcement/snmpPolicies/policy/SNMP%20policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json

RESPONSE
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating Device Group - TACACS+

```
REQUEST
POST /api/v1/configuration/uac/networkDeviceAdministration/groups/group/
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "admin-realm": "Admin Users",
    "description": "",
    "name": "Device Group"
}

RESPONSE
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or error!"
            }
        ]
    }
}
```

Deleting Device Group- TACACS+

```
REQUEST
DELETE
/api/v1/configuration/uac/networkDeviceAdministration/groups/group/Device%20Group
HTTP/1.1
Host xx.xx.xx.xx
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating TACACS+ Client

REQUEST

```
POST api/v1/configuration/uac/networkDeviceAdministration/clients/client
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "description": "",
    "deviceGroup": "Device Group",
    "enable": "true",
    "ipAddress": "10.204.88.244",
    "ipAddressRange": "1",
    "name": "TACACS client",
    "shared-secret-encrypted":
"3u+UR6n8AgABAAAAofSnIBrU19vdwUslG5LG4cg1QH6CbXDSmY4ZW0x85HY="
}
```

RESPONSE

```
{
    "result": {
        "warnings": [
            {
                "message": "The configuration has been implicitly changed"
            }
        ]
    }
}
```

Deleting TACACS+ Client

REQUEST

```
DELETE
/api/v1/configuration/uac/networkDeviceAdministration/clients/client/TACACS
%20client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

© 2020 by Pulse Secure, LLC. All rights reserved

Creating Shell Policies

REQUEST

```
POST /api/v1/configuration/uac/networkDeviceAdministration/policies/policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "apply-action": "deny",
    "apply-groups": "all",
    "apply-roles": "all",
    "commandSets": {
        "command-set": []
    },
    "defaultPrivilege": "1",
    "description": "",
    "groups": null,
    "maxPrivilege": "1",
    "name": "TACACS policy",
    "roles": null
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or error!"
            }
        ]
    }
}
```

Deleting Shell Policies

REQUEST

```
DELETE
/api/v1/configuration/uac/networkDeviceAdministration/policies/policy/TACACS%20policy
HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

RESPONSE

```
{
    "result": {
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
        "warnings": [
            {
                "message": "The configuration has been implicitly changed"
            }
        ]
    }
}
```

Creating Admission Control Client

REQUEST

```
POST  /api/v1/configuration/uac/admissionControl/clients/client HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "description": "",
    "enable": "true",
    "ipAddress": "10.204.88.12",
    "name": "FORTINET",
    "templateID": "fortigate-text.itmpl"
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or error!"
            }
        ]
    }
}
```

Deleting Admission Control Client

REQUEST

```
DELETE  /api/v1/configuration/uac/admissionControl/clients/client/FORTINET HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Creating Admission Control Policy

REQUEST

© 2020 by Pulse Secure, LLC. All rights reserved

```
POST /api/v1/configuration/uac/admissionControl/policies/policy/ HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
    "action": "ignore",
    "apply": "selected",
    "count": "1",
    "event": "utm:ips",
    "name": "policy1",
    "replacementRole": null,
    "replacementType": "Permanent",
    "roles": null,
    "severity": "critical",
    "templateID": "fortigate-text.itmpl"
}
```

RESPONSE

```
{
    "result": {
        "info": [
            {
                "message": "Operation succeeded without warning or error!"
            }
        ]
    }
```

Deleting Admission Control Policy

REQUEST

```
DELETE /api/v1/configuration/uac/admissionControl/policies/policy/policy1 HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic
VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
Content-Length: 0
Content-Type: application/json
```

Getting Authentication API Key

REQUEST

```
GET <PPS-IP Address>/api/v1/auth
```

RESPONSE

```
"api_key": "NAIq3DNqOh7aDTsXJbZRUo4b+tILb1vpf5sasdasdfao="
```

REQUEST

```
GET <PPS-IP Address>/api/v1/auth/profiler/auth
```

RESPONSE

```
"api_key": "NAIq3DNqOh7aDTsXJbZRUo4b+tILb1vpf5sasdasdfao="
```

© 2020 by Pulse Secure, LLC. All rights reserved

Pulse Policy Secure Alert Based Admission Control APIs

Checking Status of PPS Server

REQUEST

```
GET <PPS-IP Address>/api/v1/integration/status
```

RESPONSE

```
"{\"message\": \"API server is up\"}"
```

Getting Session Details for Endpoint Based on IP Address

REQUEST

```
GET <PPS-IP Address>/api/v1/integration/sessions/<endpoint-IP Address>
```

RESPONSE

```
{
  "data": [
    {
      "ip": "10.xxx.xx.xx",
      "macaddr": "00-56-65-bf-0b-cx",
      "switch_ip": "",
      "switch_port": "",
      "username": "user1"
    }
  ]
}
Note: This sample response is for Juniper SDSN.
```

Getting Session Details for Endpoint Based on MAC Address

REQUEST

```
GET <PPS-IP Address>/api/v1/integration/sessions/<endpoint-MAC Address>
```

RESPONSE

```
{
  "data": [
    {
      "macaddr": "00-56-65-bf-0b-cx",
      "switch_ip": "",
      "switch_port": "",
    }
  ]
}
```

Sending Alert Event to PPS

REQUEST

```
PUT /api/v1/ integration/sessions
For example:
Sample PUT request Payload for Juniper SDSN is {"event-name":"block-endpoint",
"srcip":"10.xxx.xx.xxx"}.
Note: The event-names and field to parse the source-IP from the event should be
```

© 2020 by Pulse Secure, LLC. All rights reserved

```
defined in the admission control template.
```

RESPONSE

```
HTTP/1.1 204 NO CONTENT
```

Profiler REST APIs

Approving Devices

REQUEST

```
PUT api/v1/profiler/endpoints/simplified/xx:xx:xx:xx:xx:xx HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
   "status": "approved"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "Successfully updated.”
}
```

Updating Device Attributes

REQUEST

```
PUT api/v1/profiler/endpoints/simplified/xx:xx:xx:xx:xx:xx HTTP/1.1
Host xx.xx.xx.xx
Authorization: Basic VU9qSTlGTzNrYVk5d0t2aXpBN1dPZ0FyZlN1S3FmTkNnQUh0R0ZuR0xSbz06
Content-Type: application/json
{
   "manufacturer": "Windows",
   "os": "Windows"
}
```

RESPONSE

```
HTTP/1.1 200 OK
Content-Type: application/json
{
  "Successfully updated.”
}
```

© 2020 by Pulse Secure, LLC. All rights reserved